Description:

Statfree® DPL Plus™ mat is made with conductive homogenous vinyl top layer laminated to an anti-fatigue foam rubber bottom layer. The product is designed to provide a flooring surface that does not generate a static charge and will act as part of the path to ground for an operator wearing ESD footwear. The resistance range (1 x 10⁴ to < 1 x 10⁶ ohms Rtt) of the top layer will remain low enough to act as a path to ground with normal dirt and grim build up on a floor and meet the required limit of ANSI/ ESD S20.20 Method 1 (<3.5 x 10⁶ ohms) for a flooring/footwear system. The bottom foam rubber layer is designed to reduce standing worker's fatigue and improve productivity. The diamond plate surface increases traction and tapered edges with radius corners help to prevent curling to improve safety in work areas.

Electrical Properties:

 Property
 Test Method
 Value

 Charge Decay:
 FTMS 101C, Method 4046
 5,000 volts-0 volts in 0.03 seconds

 Rtt Resistance:
 ANSI/ESD S7.1
 1 x 10³ to < 1 x 106 ohms</td>

 Rtg Resistance:
 ANSI/ESD S7.1
 1 x 10³ to < 1 x 106 ohms</td>

Specifications:

Construction: Conductive vinyl top layer laminated to a foam rubber bottom layer

Thickness: 0.450" (11.4mm)

Radius: 1"

Surface: Embossed Diamond Plate Design

Hardness: 90 Shore A

Heat Resistance: 0F to 150F continuous
Weight: 1.45 lbs. per square foot
Density: Average: 33 lbs. per cubic foot

<u>Grounding:</u> This material must be properly grounded for optimum electrical performance. See for Technical Bulletin <u>TB-2000</u> for mat grounding instructions. Part numbers <u>40979</u>, <u>40980</u>, <u>& 40981</u> include <u>14234</u> Grounding Kit

<u>Cleaning:</u> For optimum electrical performance, surface must be cleaned regularly using an ESD mat cleaner. We suggest using our <u>Statguard™ Floor Mat Cleaner</u>. Do not use cleaners with silicone. Silicone buildup will create an insulative film on the surface.

STATFREE DPL *PLUS™* FLOOR MAT, VINYL, CONDUCTIVE, ANTI-FATIGUE

DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: <u>Desco.com</u> PHONE (909) 627-8178 FAX (909) 627-7449

DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407 PHONE (781) 821-8370 FAX (781) 575-0172

DRAWING NUMBER

PM-125

DATE: November 2012