



+/- 1/16" tolerances on dimensions unless specified

## SPECIFICATIONS

- Dissipative Vinyl Badge Holder
  - Material Thickness: 0.012" (1S) front, & .024" (1S) back
  - Material Tolerance (thickness): ±10%
  - Material Color: matte front & back
- Highly visible yellow header with ESD protective symbol
- Includes a 1/8" x 9/16" punch through slot, setback 3/8" from top
- 4" x 3 3/8" (Outer Dimension)
- Opening setback 3/4" from top with zipper closure
- Embossing with: Menda and Made In America along the bottom of the badge holder
- Rtt: 10E6 - 10E10 ohms per ANSI/ESD S11.11
- Low Charging: < 100 volts
- Genuine Made In America - accept no substitutes
- We can do customs just let us know your insert size

*"It should be understood that any object, item, material or person could be a source of static electricity in the work environment. Removal of unnecessary nonconductors, replacing nonconductive materials with dissipative or conductive materials and grounding all conductors are the principle methods of controlling static electricity in the workplace, regardless of the activity." [ESD Handbook ESD TR20.20-2008 section 2.4 Sources of Static Electricity]*



MADE IN AMERICA

Specifications and procedures subject to change without notice.

### HORIZONTAL ESD CARD HOLDER, 3 5/8" x 2 3/8" INSERT SIZE, W/ YELLOW HEADER & ZIPPER CLOSURE

# MENDA

3651 WALNUT AVENUE, CHINO, CA 91710  
 PHONE: (909) 627-2453 FAX: (951) 755-8848  
 WEBSITE: [Menda-ID.com](http://Menda-ID.com)

**DRAWING NUMBER**  
35017

**DATE:**  
January 2011