



Features

- Efficient means of shipping or storing ESD sensitive circuit boards and other items
- Provides ESD shielding with lid closed; "Faraday Cage" effect restricts electrostatic charges to exterior
- For physical protection, convoluted foam secures items, minimizing movement and reduces stress from physical shock
- No assembly required
- Convoluted static dissipative 10^{11} ohms polyurethane pink foam laminated to top and fitted in bottom
- Available with or without foam
- Made in the United States of America

See reverse side for available sizes.

SPECIFICATIONS

Properties	Typical Values
Electrostatic Decay	0.01 seconds at 72°F and 11.8% R.H.
Surface Resistance	1×10^5 to $< 1 \times 10^{11}$ ohms
High-Voltage Discharge Resistance	Failure rate 0/5 (no oxide damage in five consecutive tests)
Static Shielding	99.9% attenuation at 10kV; 99.6% attenuation at 30kV
Current-Carrying Hazard	10^3 mA at 110V; 10^3 mA at 220V
Corrosivity	Contains 1-3 ppm reducible sulfur
Antistat Transfer	No transfer
Water & Isopropyl Alcohol Extraction Tests for Antistat Permanence	Surface resistance 10^8 - 10^9 ohms/square at 74°F and 36% R.H.
Sloughing Test	Negligible surface damage at 10 cycles and <5% of surface damage at 200 cycles in Taber Abrasion Test. No conductive particles abraded from surface
Recyclability	Complete recyclability of package
Biodegradability	Biodegradation in or on moist soil
Volume Conductivity	Conductivity from wall to wall as well as across surface to assure permanence of the antistatic property
Shelf Life	Indefinite

Test Procedures/Method

FED-STD-101, Method 4046
 ANSI/ESD STM11.11
 Rockwell International Test Report of December 20, 1991
 EIA 541, appendix E, capacitive probe test
 ESD from A to Z
 FED-STD-101, Method 3005 for reducible sulfur
 Rockwell International Test Report of January 8, 1992
 Rockwell International Test Report of January 8, 1992

 ASTM D4060 at 70 rpm with CS-17 abrasive-coated wheels and 1000 grams load
 Rockwell International Test Report of January 8, 1992
 Rockwell International Test Report of January 8, 1992

 Rockwell International Test Report of January 8, 1992



CIRCUIT BOARD SHIPPERS

Specifications and procedures subject to change without notice.

PROTEKTIVE PAK

PROTEKTIVE PAK
 1350 MONTE VISTA AVENUE, CHINO, CA 91710
 PHONE (909) 627-2578, FAX (909) 363-7331
 ProtektivePak.com

DRAWING NUMBER
 37050

DATE:
 December
 2013

Item No.	Size I.D. - L x W x D
37050	4 x 4 x 2-1/8, box only
37051	4 x 4 x 2-1/8, box w/foam
37080	6-3/16 x 6 x 1-1/2, box only
37081	6-3/16 x 6 x 1-1/2, box w/ foam
37052	7 x 5 x 1-1/2, box only
37053	7 x 5 x 1-1/2, box w/ foam
37054	7 x 5 x 2-1/2, box only
37055	7 x 5 x 2-1/2, box w/ foam
37082	7 x 7 x 1-1/2, box only
37083	7 x 7 x 1-1/2, box w/ foam
37056	9 x 7-1/2 x 2-1/2, box only
37057	9 x 7-1/2 x 2-1/2, box w/foam
37084	9 x 9 x 1-1/2, box only
37085	9 x 9 x 1-1/2, box w/foam
37058	10-1/2 x 8-1/2 x 1-1/2, box only
37059	10-1/2 x 8-1/2 x 1-1/2, box w/foam
37060	10-1/2 x 8-1/2 x 2-1/2, box only
37061	10-1/2 x 8-1/2 x 2-1/2, box w/foam
37062	12-1/2 x 10-1/2 x 1-1/2, box only
37063	12-1/2 x 10-1/2 x 1-1/2, box w/foam
37064	12-1/2 x 10-1/2 x 2-1/2, box only
37065	12-1/2 x 10-1/2 x 2-1/2, box w/foam

Item No.	Size I.D. - L x W x D
37066	14-7/8 x 6-5/8 x 2, box only
37067	14-7/8 x 6-5/8 x 2, box w/foam
37068	15-1/2 x 12-1/2 x 1-1/2, box only
37069	15-1/2 x 12-1/2 x 1-1/2, box w/foam
37070	15-1/2 x 12-1/2 x 2-1/2, box only
37071	15-1/2 x 12-1/2 x 2-1/2, box w/foam
37072	16 x 12-1/4 x 3-1/2, box only
37073	16 x 12-1/4 x 3-1/2, box w/foam
37086	16 x 15 x 3, box only
37087	16 x 15 x 3, box w/foam
37074•	18-7/8 x 17-5/8 x 1-3/4, box only
37075•	18-7/8 x 17-5/8 x 1-3/4, box w/foam
37088•	19 x 19 x 3, box only
37089•	19 x 19 x 3, box w/foam
37076•	20-1/2 x 15-1/2 x 1-1/2, box only
37077•	20-1/2 x 15-1/2 x 1-1/2, box w/foam
37078	20-1/2 x 15-1/2 x 2-1/2, box only
37079	20-1/2 x 15-1/2 x 2-1/2, box w/foam
37090•	22 x 15 x 3, box only
37091•	22 x 15 x 3, box w/foam
37092•	27-3/8 x 24-3/8 x 4, box only
37093•	27-3/8 x 24-3/8 x 4, box w/foam

- These items made to order