



Speaker and Control Cable

Multi-Conductor, Shielded, Plenum

NEC Type CL3P (UL) and/or NEC Type CMP (UL) c(UL)

PLENUM CABLE - PVC INSULATION, PVC JACKET

| CATALOG NUMBER | NO. OF COND. | AWG SIZE | COND. STRAND | Nom. Insulation Wall | | Nom. Jacket Wall | | NOMINAL O.D. | | NEC TYPE |
|--------------------------|--------------|----------|--------------|----------------------|------|------------------|------|--------------|------|------------|
| | | | | Inches | mm | Inches | mm | Inches | mm | |
| 22 AWG CONDUCTORS | | | | | | | | | | |
| SSS222P | 2 | 22 | 7/30 | 0.008 | 0.20 | 0.015 | 0.38 | 0.128 | 3.25 | CL3P & CMP |
| SSS224P | 4 | 22 | 7/30 | 0.008 | 0.20 | 0.015 | 0.38 | 0.147 | 3.73 | CL3P & CMP |
| 20 AWG CONDUCTORS | | | | | | | | | | |
| SSS202P | 2 | 20 | 7/28 | 0.008 | 0.20 | 0.015 | 0.38 | 0.139 | 3.53 | CL3P & CMP |
| SSS204P | 4 | 20 | 7/28 | 0.008 | 0.20 | 0.015 | 0.38 | 0.161 | 4.09 | CL3P & CMP |
| 18 AWG CONDUCTORS | | | | | | | | | | |
| SSS182P | 2 | 18 | 7/26 | 0.008 | 0.20 | 0.015 | 0.38 | 0.159 | 4.04 | CL3P & CMP |
| SSS184P | 4 | 18 | 7/26 | 0.008 | 0.20 | 0.015 | 0.38 | 0.185 | 4.70 | CL3P & CMP |
| 16 AWG CONDUCTORS | | | | | | | | | | |
| SSS162P | 2 | 16 | 19/.0117 | 0.008 | 0.20 | 0.015 | 0.38 | 0.179 | 4.55 | CL3P & CMP |
| SSS164P | 4 | 16 | 19/.0117 | 0.008 | 0.20 | 0.015 | 0.38 | 0.209 | 5.31 | CL3P & CMP |
| 14 AWG CONDUCTORS | | | | | | | | | | |
| SSS142P | 2 | 14 | 19/.0147 | 0.008 | 0.20 | 0.015 | 0.38 | 0.207 | 5.26 | CL3P |
| SSS144P* | 4 | 14 | 19/.0147 | 0.008 | 0.20 | 0.015 | 0.38 | 0.260 | 6.60 | CL3P |
| 12 AWG CONDUCTORS | | | | | | | | | | |
| SSS122P | 2 | 12 | 19/.0185 | 0.008 | 0.20 | 0.015 | 0.38 | 0.244 | 6.20 | CL3P |
| SSS124P* | 4 | 12 | 19/.0185 | 0.008 | 0.20 | 0.015 | 0.38 | 0.288 | 7.32 | CL3P |

PRODUCT CONSTRUCTION

Conductor:

- Stranded bare copper per ASTM B-3

Insulation:

- CMP - Plenum PVC

Shield:

- 100% Foil Shield
- Stranded Tinned Copper Drain

Jacket:

- CMP - Plenum PVC

Jacket Color:

- CMP - White (Natural)

APPLICATIONS

- Power-limited control circuits
- Wiring of the following systems:
 - Intercom
 - Security
 - Audio
 - Background Music

PACKAGING

- 500 ft. or 1000 ft. Boxes & Reels
- *Reels only

Color Code Chart

| NO OF. COND. | COLOR |
|--------------|-------|
| 1 | Black |
| 2 | Red |
| 3 | White |
| 4 | Green |

