

DS460S

460 Watts

Distributed Power System

Distributed Power Bulk Front-End

Total Output Power: 460 Watts

+12 Vdc Stand-by Output

Wide Range Input Voltage: 90 - 264 Vac



Special Features

- Active power factor correction
- EN61000-3-2 harmonic compliance
- Active AC inrush control
- 1U X 2U form factor
- +12 Vdc output
- +12 Vdc stand-by
- Hot plug operation
- N + 1 redundant
- Active current sharing
- Built-in cooling fan
- I²C communication interface bus
- PMBus compliant
- EEPROM for FRU data
- One year warranty

Electrical Specifications

| Input | |
|------------------------|--|
| Input range: | 90 - 264 |
| Frequency: | 47 - 63 Hz, single phase AC |
| Inrush current: | 30 Apk maximum inrush current |
| Efficiency: | 92% typical at high line 50% load |
| Conducted EMI: | FCC Subpart J EN55022 Class B |
| Radiated EMI: | FCC Subpart J EN55022 Class B |
| Power factor: | 0.99 typical |
| Leakage current: | 1.0 mA @ 240 Vac |
| Hold up time: | 10 ms minimum |
| Output | |
| Main DC voltage: | +12.3 V @ 36.0 A |
| Stand-By: | +12 V @ 2.3 A |
| Adjustment range: | Factory set |
| Regulation: | 11.85 - 12.45 Vdc 11.40 - 12.6 Vdc |
| Overcurrent: | +12 Vdc; latches off if overcurrent lasts over 1 second, Trip point 120% - 150% of rated current. |
| Overvoltage: | +12 Vdc; 13.6 - 15.0 Vdc +12 Vsb; 13.6 - 15.0 Vdc |
| Turn-on delay: | 1 - 1.5 seconds |
| Main output rise time: | 10 - 30 mS, monotonic rise |

Safety

- UL/cUL 60950 (UL Recognized)
- NEMKO 60950
- Cb Certificate and report
- CE Mark (LVD)

Logic Control

| | |
|--------------------|--|
| PS_PRESENT (S4): | Used to sense the number of power supplies in the system (operational or not) and provide hot plug insertion and removal functionality by controlling main outputs during hot plug insertion and removal by employing following circuitry. When the unit is removed from the system the fast shut down signal quickly turns OFF main outputs and discharges output capacitors. This signal is the shortest gold finger pin on the signal connector to allow for last make, first break configuration. |
| PSOK (S6): | Combined indicator of AC input and main 12 V DC output. This is a three level signal to indicate different stages as follows. AC not OK and DC not OK – Signal status shall be LOW (< 0.6 V) AC OK and DC not OK – Signal status shall be LOW (< 0.6 V) AC OK and DC OK – Signal status shall be HIGH (> 3.0 V) AC not OK and DC OK – Signal status shall be Middle Level (Between 2 V and 2.5 V) DC OK threshold is defined as when the 12 V output is greater than 11.5 V. DC not OK threshold is defined as when the 12 V output is less than 11.4 V & greater than 11.3 V. |
| I-Mon (S7): | Provides both the load sharing function (as a feedback for output regulation droop function) and 12 V output current information. |
| PS INTERRUPT (S4): | The signal behavior in response to certain operating condition changes in the power supply as defined in the Firmware Specification section. This signal shall be pulled up to maximum 5 V logic level external to the PS. |
| PS ON (S8): | Required to remotely turn on/off the power supply. PSON# is an active low signal that turns on the main 12 V DC output. When this signal is not pulled low by the system, or left open, the 12 V output is turned off. This signal is pulled to a standby voltage by a pull-up resistor internal to the power supply. Refer to On/Off Timing for timing diagram in TRN. When in off or standby condition, the main 12 V DC output will be less than 50 mV with respect to output return. |

Environmental Specifications

| | |
|--|---|
| Operating temperature: | -10° to 50 °C |
| Storage temperature: | -40 °C to +85 °C |
| Altitude, operating: | 10,000 ft |
| Electromagnetic susceptibility / Input transients: | -EN61000-3-2 -EN61000-4-2, 4.3, 4-4, -4-5, 4-6, 4-11 |
| RoHS & lead-free compliant: | No tantalum caps. |
| Humidity: | 5 to 90% RH, non-condensing |
| Shock and vibration specifications: | Complies with Astec Std. Specifications, Q3205 |
| MTBF (Demonstrated): | 500K Hrs at full load, 50 °C |


Ordering Information

| Model Number | Nominal Output Voltage Set Point | Set Point Tolerance | Total Regulation | Minimum Current | Maximum Current | Output Ripple P/P | Over Current | Stand-by | Air Flow |
|--------------|----------------------------------|---------------------|------------------|-----------------|-----------------|-------------------|------------------|----------------|----------|
| DS460S-3-002 | 12.3 Vdc | ± 0.2% | ± 5% | 1 A | 36.0 A | 120 mV | 45.9 A - 57.5 A* | 12.0 V @ 2.3 A | STD |
| DS460S-3-003 | 12.3 Vdc | ± 0.2% | ± 5% | 1 A | 36.0 A | 120 mV | 45.9 A - 57.5 A* | 12.0 V @ 2.3 A | REV |

*Overcurrent latches off if overcurrent lasts over 1 seconds, otherwise it is auto recovery.

Mechanical Drawing


Weight: 1.88 lbs



Connector Definitions


AC Input Connector

| | |
|-------|-------------|
| Pin 1 | Line |
| Pin 2 | Neutral |
| Pin 3 | Eath Ground |




Output Connector - Power Blades

| | |
|------|----------------|
| PB1 | V _O |
| PB2 | V _O |
| PB3 | V _O |
| PB4 | RTN |
| PB5 | RTN |
| PB6 | RTN |
| PB7 | RTN |
| PB8 | RTN |
| PB9 | V _O |
| PB10 | V _O |



Output Connector - Signal Blades

| | |
|-----|--------------|
| S1 | VSB |
| S2 | VSB |
| S3 | Reserved |
| S4 | PS INTERRUPT |
| S5 | PS PRESENT |
| S6 | PSOK |
| S7 | I-MON |
| S8 | PSO# |
| S9 | SCL* |
| S10 | SDA |
| S11 | GND |
| S12 | ADD0 |
| S13 | ADD1 |
| S14 | ADD2 |
| S15 | RTN |
| S16 | RTN |



*Supports I²C standard mode (100 kHz) only

Americas

5810 Van Allen Way
Carlsbad, CA 92008
USA
Telephone: +1 760 930 4600
Facsimile: +1 760 930 0698

Europe (UK)

Waterfront Business Park
Merry Hill, Dudley
West Midlands, DY5 1LX
United Kingdom
Telephone: +44 (0) 1384 842 211
Facsimile: +44 (0) 1384 843 355

Asia (HK)

14/F, Lu Plaza
2 Wing Yip Street
Kwun Tong, Kowloon
Hong Kong
Telephone: +852 2176 3333
Facsimile: +852 2176 3888

For global contact, visit:

www.Emerson.com/EmbeddedPower
techsupport.embeddedpower@emerson.com

While every precaution has been taken to ensure accuracy and completeness in this literature, Emerson Network Power assumes no responsibility, and disclaims all liability for damages resulting from use of this information or for any errors or omissions.

Emerson Network Power.
The global leader in enabling
business-critical continuity.

- AC Power
- Connectivity
- DC Power
- Embedded Computing
- **Embedded Power**
- Monitoring
- Outside Plant
- Power Switching & Controls
- Precision Cooling
- Racks & Integrated Cabinets
- Services
- Surge Protection

EmersonNetworkPower.com

Emerson Network Power and the Emerson Network Power logo are trademarks and service marks of Emerson Electric Co. ©2011 Emerson Electric Co.

Power/Signal Mating Connectors and Pin Types

| Reference | On Power Supply | Mating Connector or Equivalent |
|--------------------|------------------------|--------------------------------|
| AC Input Connector | IEC320-C13 | IEC320-C14 |
| Output Connector | PCB card edge (0.062") | Molex 459840007 (top mount) |
| | | Molex 459841122 (bottom mount) |