


周黑

**B30D3FCH-E7**




## Features

- Package: RGB 3 in 1 package/4pin Polarity
- Anti-Reflection resin
- View angle :  $\geq 120^\circ$  (min 50% brightness)
- Component solder able surface finish is gold
- High contrast

## Main Applications

- Indoor display
- Full color display
- Fine pitch application



DISCLAIMER.....	3
PRODUCT SPECIFICATIONS.....	4
<b>ATTENTION: ELECTROSTATIC DISCHARGE (ESD) PROTECTION</b> .....	5
LABEL SPECIFICATIONS.....	5
SPECIFICATIONS RANGE.....	7
PRODUCT FEATURES .....	8
ELECTRO-OPTICAL CHARACTERISTICS.....	8
<b>PACKAGE OUTLINE DIMENSION AND RECOMMENDED SOLDERING PATTERN FOR REFLOW</b>	
<b>SOLDERING</b> .....	8
<b>ABSOLUTE MAXIMUM RATINGS</b> .....	8
<b>CHARACTERISTICS OF B30D3FCH-E7</b> .....	9
PRECAUTION FOR USE.....	10
PACKAGING .....	11
<b>TAPE DIMENSION</b> .....	11
<b>REEL DIMENSION</b> .....	12
<b>PACKING</b> .....	12
DRY PACK.....	13
<b>BAKING</b> .....	13
PRECAUTIONS.....	13
REFLOW SOLDERING .....	14
<b>REWORKING</b> .....	14
<b>CLEANING</b> .....	14
<b>REVISE HISTORY</b> .....	15

Official Product	HT Part No. B30D3FCH-E7	Customer Part No.		Data Sheet No.
Tentative Product	*****	*****		
Specifications are subject to changes for improvement without advance notice. Proprietary data, drawings, company confidential all rights reserved.		10/25/2013	Version 1.0	Page 2/15

**DISCLAIMER**

HARVATEK reserves the right to make changes without further notice to any products herein to improve reliability, function or design. HARVATEK does not assume any liability arising out of the application or use of any product or circuit described herein; neither does it convey any license under its patent rights, nor the rights of others.

**LIFE SUPPORT POLICY**

HARVATEK's products are not authorized for use as critical components in life support devices or systems without the express written approval of the President of HARVATEK or HARVATEK INTERNATIONAL. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

---

Official Product	HT Part No. B30D3FCH-E7	Customer Part No.		Data Sheet No.
Tentative Product	*****	*****		
Specifications are subject to changes for improvement without advance notice. Proprietary data, drawings, company confidential all rights reserved.		10/25/2013	Version 1.0	Page 3/15

## Product Specifications

	Specification	Material	Quantity
Luminous Intensity(Iv)	Red : 42 mcd typical Green : 55 mcd typical Blue : 11.5 mcd typical R@10mA;G/B@5mA/ Ts= 25 <sup>o</sup> C; Tolerance ±10%		
Wavelength	Red : 622 nm typical Green : 530 nm typical Blue : 471 nm typical R@10mA;G/B@5mA/ Ts= 25 <sup>o</sup> C;Tolerance ± 0.5nm		
Vf	Red : 2.4 V maximum Green : 3.4 V maximum Blue : 3.4 V maximum R@10mA;G/B@5mA/ Ts= 25 <sup>o</sup> C;Tolerance ± 0.05V		
Ir	< 100 μA @ V <sub>R</sub> = 5 V		
Resin	Dark	Epoxy	
Carrier tape	EIA 481-1A specs	Conductive black tape	4000pcs/reel
Reel	EIA 481-1A specs	Conductive black	
Label	HT standard	Paper	
Packing bag	250x230mm	Aluminum laminated bag/ no-zipper	One reel per bag
Carton	HT standard	Paper	Non-specified

Official Product	HT Part No. B30D3FCH-E7	Customer Part No.		Data Sheet No.
Tentative Product	*****	*****		
Specifications are subject to changes for improvement without advance notice. Proprietary data, drawings, company confidential all rights reserved.		10/25/2013	Version 1.0	Page 4/15

Others:

Each immediate box consists of 5 reels. The 5 reels may not necessarily have the same lot number or the same bin combinations of  $I_v$ ,  $\lambda_D$  and  $V_f$ . Each reel has a label identifying its specification; the immediate box consists of a product label as well.

Note :This is shipped test conditions

※Remarks: This product should be operated in forward bias. If a reverse voltage is continuously applied to the product, such operation can cause migration resulting in LED damage.


### ATTENTION: Electrostatic Discharge (ESD) protection



The symbol to the left denotes that ESD precaution is needed. ESD protection for GaP and AlGaAs based chips is necessary even though they are relatively safe in the presence of low static-electric discharge. Parts built with AlInGaP, GaN, or/and InGaN based chips are **STATIC SENSITIVE devices**. ESD precaution must be taken during design and assembly.


If manual work or processing is needed, please ensure the device is adequately protected from ESD during the process.

### Label Specifications



Official Product	HT Part No. B30D3FCH-E7	Customer Part No.		Data Sheet No.
Tentative Product	*****	*****		
Specifications are subject to changes for improvement without advance notice. Proprietary data, drawings, company confidential all rights reserved.		10/25/2013	Version 1.0	Page 5/15

■ Harvatek P/N:



■ Lot No.

1	2	3	4	5	6	7	8	9	10
<b>E</b>	<b>1</b>	<b>A</b>	<b>1</b>	<b>A</b>	<b>2</b>	<b>2</b>	<b>L</b>	<b>1</b>	<b>2</b>
Code 1 2		Code 3	Code 4	Code 5	Code 6	Code 7	Code 8	Code 9	Code 10
		Mfg. Year	Mfg. Month	Mfg. Date	Consecutive number		Special code		
Internal Tracing Code		2010-A 2011-B 2012-C 2013-D . .	1:Jan. 2:Feb. ... A:Oct. B:Nov. C:Dec.	1:A 2:B 3:C ... 26:Z 27:7 28:8 29:9 30:3 31:4	01~ZZ		000~ZZZ		

Official Product	HT Part No. B30D3FCH-E7	Customer Part No.		Data Sheet No.
Tentative Product	*****	*****		
Specifications are subject to changes for improvement without advance notice. Proprietary data, drawings, company confidential all rights reserved.		10/25/2013	Version 1.0	Page 6/15

## Specifications Range

### ■ Luminous Intensity (Iv) Bin:

Luminous Intensity (Iv) Bin: R@10mA;G/B @5mA

HT-B30D3FCH Series								
IV								
Red			Green			Blue		
FJ2	30.3	36.4	FK1	36.4	43.7	FD3	8.4	10
FJ3	32.7	39.3	FK2	39.3	47.2	FE1	9	10.8
FK1	36.4	43.7	FK3	43.7	52.5	FE2	10	12
FK2	39.3	47.2	FL1	47.2	56.7	FE3	10.8	13
FK3	43.7	52.5	FL2	52.5	63	FF1	12	14.5
FL1	47.2	56.7	FL3	56.7	68.5	FF2	13	15.6
FL2	52.5	63	FM1	63	75.6	FF3	14.5	17.5

Note: It maintains a tolerance of ±10% on Luminous Intensity

### Dominant Wavelength (λD) Bin:

HT-B30D3FCH Series								
WD								
Red			Green			Blue		
R1	616	620	G1	523	526	B1	464	467
R2	620	624	G2	526	529	B2	467	470
R3	624	628	G3	529	532	B3	470	473
R4	628	632	G4	532	535	B4	473	476
			G5	535	538	B5	476	479
			G6	538	541			

Note: It maintains a tolerance of ±0.5nm on Color Bin

### Forward Voltage (Vf) Bin:

HT-B30D3FCH Series								
Vf								
Red			Green			Blue		
-	1.6	2.4	-	2.4	3.4	-	2.4	3.4

Note: It maintains a tolerance of ±0.05V on forward voltage measurements

Official Product	HT Part No. B30D3FCH-E7	Customer Part No.		Data Sheet No.
Tentative Product	*****	*****		
Specifications are subject to changes for improvement without advance notice. Proprietary data, drawings, company confidential all rights reserved.		10/25/2013	Version 1.0	Page 7/15

### Product Features

### Electro-Optical Characteristics

(T<sub>Soldering</sub>, 25 °C)

Part number	Emitting Color	Forward Voltage(VF)		Wavelength (nm) typ.			I <sub>V</sub> (mcd) typ.	Viewing Angle 2θ1/2
		typ.	max.	λD	λp	Δλ		
HT-B30D3FCH-E7	Ultra Bright Red	1.9	2.4	622	629	16	42	140
	Green	2.7	3.4	530	520	32	55	140
	Blue	2.7	3.4	471	480	22	11.5	140

### Package Outline Dimension and Recommended Soldering Pattern for Reflow Soldering

Unit: mm Tolerance: +/-0.1

Outline Dim.	Soldering Pattern
Soldering terminals may shift in the x, y direction.	

### Absolute Maximum Ratings

(T<sub>S</sub> 25 °C)


Series	P <sub>D</sub> (mW)	I <sub>F</sub> (mA)	I <sub>FP</sub> (mA)	T <sub>OP</sub> (°C)	T <sub>ST</sub> (°C)
Color	Power Dissipation	Forward Current	Pulse Forward Current	Color	Power Dissipation
Red	150	10	100	-30~+80	-40~+85
Blue/Green		5			

\*\* Condition for I<sub>FP</sub> is pulse of 1/10 duty and 0.1msec width


Official Product	HT Part No. B30D3FCH-E7	Customer Part No.	Data Sheet No.
Tentative Product	*****	*****	
Specifications are subject to changes for improvement without advance notice. Proprietary data, drawings, company confidential all rights reserved.		10/25/2013	Version 1.0
			Page 8/15

### Characteristics of B30D3FCH-E7


Relative Intensity vs. Forward Current






Forward Voltage vs. Forward Current



Forward Current vs. Ambient Temperature



Wavelength vs. Forward Current




Official Product	HT Part No. B30D3FCH-E7	Customer Part No.	Data Sheet No.
Tentative Product	*****	*****	
Specifications are subject to changes for improvement without advance notice. Proprietary data, drawings, company confidential all rights reserved.	10/25/2013	Version 1.0	Page 9/15

### Precaution for Use

1. The chips should not be used directly in any type of fluid such as water, oil, organic solvent, etc.
2. When the LEDs are illuminating, the maximum ambient temperature should be first considered before operation.
3. LEDs must be stored in a clean environment. A sealed container with a nitrogen atmosphere is necessary if the storage period is over 3 months after shipping.
4. The LEDs must be used within seven days after unpacked. Unused products must be repacked in an anti-electrostatic package, folded to close any opening and then stored in a dry and cool space.
5. The appearance and specifications of the products may be modified for improvement without further notice.
6. The LEDs are sensitive to the static electricity and surge. It is strongly recommended to use a grounded wrist band and anti-electrostatic glove when handling the LEDs. If a voltage over the absolute maximum rating is applied to LEDs, it will damage LEDs. Damaged LEDs will show some abnormal characteristics such as remarkable increase of leak current, lower turn-on voltage and getting unlit at low current.


Official Product	HT Part No. B30D3FCH-E7	Customer Part No.		Data Sheet No.
Tentative Product	*****	*****		
Specifications are subject to changes for improvement without advance notice. Proprietary data, drawings, company confidential all rights reserved.		10/25/2013	Version 1.0	Page 10/15

**Packaging**  
**Tape Dimension**




Dim. A	Dim. B	Dim. C	Q'ty/Reel
1.18±0.05	1.18±0.05	0.78±0.05	4K

nit: mm




Official Product	HT Part No. B30D3FCH-E7	Customer Part No.	Data Sheet No.
Tentative Product	*****	*****	
Specifications are subject to changes for improvement without advance notice. Proprietary data, drawings, company confidential all rights reserved.		10/25/2013	Version 1.0
			Page 11/15

### Reel Dimension



### Packing



5 boxes per carton is available depending on shipment quantity.


Official Product	HT Part No. B30D3FCH-E7	Customer Part No.	Data Sheet No.
Tentative Product	*****	*****	
Specifications are subject to changes for improvement without advance notice. Proprietary data, drawings, company confidential all rights reserved.		10/25/2013	Version 1.0
			Page 12/15

## Dry Pack

All SMD optical devices are **MOISTURE SENSITIVE**. Avoid exposure to moisture at all times during transportation or storage. Every reel is packaged in a moisture protected anti-static bag. Each bag is properly sealed prior to shipment.

Upon request, a humidity indicator will be included in the moisture protected anti-static bag prior to shipment.

The packaging sequence is as follows:



## Baking

Baking before soldering is recommended when the package has been unsealed for 72hours.

The conditions are as followings:

1.  $60\pm 3^{\circ}\text{C} \times (12\sim 24\text{hrs})$  and  $<5\%RH$ , taped reel type.
2.  $100\pm 3^{\circ}\text{C} \times (45\text{min}\sim 1\text{hr})$ , bulk type.
3.  $130\pm 3^{\circ}\text{C} \times (15\text{min}\sim 30\text{min})$ , bulk type.

## PRECAUTIONS

1. Avoid exposure to moisture at all times during transportation or storage.
2. Anti-Static precaution must be taken when handling GaN, InGaN, and AlInGaP products.
3. It is suggested to connect the unit with a current limiting resistor of the proper size. Avoid applying a reverse voltage beyond the specified limit.
4. Avoid operation beyond the limits as specified by the absolute maximum ratings.
5. Avoid direct contact with the surface through which the LED emits light.
6. If possible, assemble the unit in a clean room or dust-free environment.

Official Product	HT Part No. B30D3FCH-E7	Customer Part No.	Data Sheet No.
Tentative Product	*****	*****	
Specifications are subject to changes for improvement without advance notice. Proprietary data, drawings, company confidential all rights reserved.		10/25/2013	Version 1.0
			Page 13/15


## Reflow Soldering

Recommend soldering paste specifications:

1. Operating temp.: Above 220 °C ,60sec
2. Peak temp.:260 °CMax.,10sec Max.
3. Never take next process until the component is cooled down to room temperature after reflow.
4. The recommended reflow soldering profile (measuring on the surface of the LED terminal) is following:

Lead-free Solder Profile

5. Reflow soldering should not be done more than two times



## Reworking

- Rework should be completed within 5 seconds under 260 °C.
- The iron tip must not come in contact with the copper foil.
- Twin-head type is preferred.

## Cleaning

Following are cleaning procedures after soldering:

- An alcohol-based solvent such as isopropyl alcohol (IPA) is recommended.
- Temperature x Time should be 50°C x 30sec. or <30°C x 3min
- Ultra sonic cleaning: < 15W/ bath; bath volume ≤ 1liter
- Curing: 100 °C max, <3min

Official Product	HT Part No. B30D3FCH-E7	Customer Part No.	Data Sheet No.
Tentative Product	*****	*****	
Specifications are subject to changes for improvement without advance notice. Proprietary data, drawings, company confidential all rights reserved.		10/25/2013	Version 1.0
			Page 14/15

