



MTPS160 Series

160 Watt, Medical Grade Universal Input, Desktop Adapter

INPUT SPECIFICATIONS

All specifications are typical at nominal input, full load.

INPUT SPECIFICATIONS

Input Voltage	AC 100 – 240VAC
Input Frequency	50 – 60Hz
Input Current	1.8A – 0.9A
Protection	Internal Primary Current Fuse Inrush Limiting

OUTPUT SPECIFICATIONS

Output Voltage	See Chart
Efficiency	CEC Level V, ErP Stage 2
Protection	Short Circuit Protection Over Current Protection Over Voltage Protection Over Temperature Protection
Ripple	1 – 2 % Vp-p (max)
Hold-Up Time	10 mS (min)
Transient Response	0.5mS for 50% Load Change(typ)
Load Regulation	± 5% (typ)
Leakage Current	0.50mA @ 3 pin

GENERAL SPECIFICATIONS

MTBF(Calculated)	300,000 Hours Calculated hours at 25 °C by Telecordia SR-332
Dielectric Withstanding Voltage	4,000 VAC Primary – Secondary
EMI Conduction & Radiation	Compliance to EN55011 Class B
Harmonic Current	Compliance to EN61000-3-2
EMS Immunity	Compliance to EN60601-1-2
Safety Approvals	CB/UL/cUL/FCC/CE/TUV



FEATURES

- *ES60601-1:2005 (60601 3rd EDITION)*
- *UNIVERSAL INPUT (AC100-240V)*
- *OVERVOLTAGE PROTECTION*
- *OVERCURRENT PROTECTION*
- *ROHS COMPLIANT*
- *CEC LEVEL V*

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	0 °C~+40 °C
Storage Temperature	-20 °C ~ +80 °C
Cooling.	Convection
Operating Humidity	20 – 80% Rh
Storage Humidity	10 – 90% Rh

MECHANICAL SPECIFICATIONS

Case Dimension	L183 x W81 x H42 (mm)
Input Configuration	IEC320-C14 Optional C6
DC Cord	16AWG
Output Connector	DIN



MTPS160 Series

Model Number	Output Voltage	Output Current	Max Output Power
MTPS160-1212DT-3P	12.0V	12.5A	160W
MTPS160-1984DT-3P	19.0V	8.4A	160W
MTPS160-2466DT-3P	24.0V	6.6A	160W
MTPS160-4833DT-3P	48.0V	3.3A	160W

Mechanical Drawing:

