
ePH1200

**Handwriting
Recognition
Microcontroller**

Product Specification

Doc. VERSION 2.0

ELAN MICROELECTRONICS CORP.


June 2005



Trademark Acknowledgments:

IBM is a registered trademark and PS/2 is a trademark of IBM.

Windows is a trademark of Microsoft Corporation.

ELAN and ELAN logo  are trademarks of ELAN Microelectronics Corporation.

Copyright © 2005 by ELAN Microelectronics Corporation

All Rights Reserved

Printed in Taiwan, ROC

The contents of this specification are subject to change without further notice. ELAN Microelectronics assumes no responsibility concerning the accuracy, adequacy, or completeness of this specification. ELAN Microelectronics makes no commitment to update, or to keep current the information and material contained in this specification. Such information and material may change to conform to each confirmed order.

In no event shall ELAN Microelectronics be made responsible for any claims attributed to errors, omissions, or other inaccuracies in the information or material contained in this specification. ELAN Microelectronics shall not be liable for direct, indirect, special incidental, or consequential damages arising from the use of such information or material.

The software (if any) described in this specification is furnished under a license or nondisclosure agreement, and may be used or copied only in accordance with the terms of such agreement.

ELAN Microelectronics products are not intended for use in life support appliances, devices, or systems. Use of ELAN Microelectronics product in such applications is not supported and is prohibited.

NO PART OF THIS SPECIFICATION MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS WITHOUT THE EXPRESSED WRITTEN PERMISSION OF ELAN MICROELECTRONICS.



ELAN MICROELECTRONICS CORPORATION

Headquarters:

No. 12, Innovation Road 1
Hsinchu Science Park
Hsinchu, Taiwan, R.O.C. 30077
Tel: +886 3 563-9977
Fax: +886 3 563-9966
<http://www.emc.com.tw>

Hong Kong:

Elan (HK) Microelectronics Corporation, Ltd.
Rm. 1005B, 10/F Empire Centre
68 Mody Road, Tsimshatsui
Kowloon, HONG KONG
Tel: +852 2723-3376
Fax: +852 2723-7780
elanhk@emc.com.hk

USA:

Elan Information Technology Group
1821 Saratoga Ave., Suite 250
Saratoga, CA 95070
USA
Tel: +1 408 366-8223
Fax: +1 408 366-8220

Europe:

Elan Microelectronics Corp. (Europe)

Siewerdtstrasse 105
8050 Zurich, SWITZERLAND
Tel: +41 43 299-4060
Fax: +41 43 299-4079
<http://www.elan-europe.com>

Shenzhen:

Elan Microelectronics Shenzhen, Ltd.

SSMEC Bldg., 3F, Gaoxin S. Ave.
Shenzhen Hi-Tech Industrial Park
Shenzhen, Guangdong, CHINA
Tel: +86 755 2601-0565
Fax: +86 755 2601-0500

Shanghai:

Elan Microelectronics Shanghai Corporation, Ltd.

23/Bldg. #115 Lane 572, Bibo Road
Zhangjiang Hi-Tech Park
Shanghai, CHINA
Tel: +86 021 5080-3866
Fax: +86 021 5080-4600

Contents

1	Introduction	1
2	Features	1
3	Block Diagram	1
4	Pin Assignment	2
4.1	LQFP 44 Pin	2
4.2	CSP (Chip Size Package) 24 Pin	3
4.3	Ordering Information	4
5	Pin Description	4
6	Interface Control Timing Description	5
6.1	UART Interface Control (9600, N, 8, 1)	5
7	Pin Option Description	6
7.1	CE Pin Option	6
7.2	ECR Pin Option	6
8	Electrical Characteristic	7
8.1	Absolute Maximum Ratings	7
8.2	Recommended Operating Conditions	7
8.3	DC Electrical Characteristics (Condition: Ta=25° C, VDD= 3.0 +/- 0.3V)	7
8.4	A/D Conversion (VDD=3.0V, VDDA=3.0V, Ta=25° C, Fclk=12*Fsample)	8
8.5	AC Electrical Characteristics (Condition: Ta=25° C, VDD=3.0 +/- 0.3V)	8
9	Power-up and Reset Timing	9
10	Application Circuit	10
10.1	UART Interface Application Circuit (with 32.768KHz Crystal)	10
10.1.1	BOM Table	10
10.2	UART Interface Application Circuit (with 32.768KHz External Clock)	11
10.2.1	BOM Table	11
10.3	Touch Panel and YP, XP, YN, & XN Layout Format	12
11	HWRE Software Specification	13
11.1	HWRE Software Description	13
11.2	Communication Protocol and Command List	13
11.2.1	Communication Interface: UART	13
11.2.2	Command Timing Request	13
11.2.3	Commands from Host (see Section 11.3 for details)	14
11.2.4	Responses from ePH1200 (see Section 11.4 for details)	14



11.3	Commands from Host Specifications	15
11.3.1	Wake up ePH1200 (0x33; 8 Bytes).....	15
11.3.2	Set Character Recognition Mode (0x10; 8 Bytes).....	15
11.3.3	Set Inking Transmit Switch (0x14; 8 Bytes)	17
11.3.4	Set Pen Up (Lifting of Stylus) Waiting Time (0x1A; 8 Bytes).....	17
11.3.5	Perform Recognition Immediately, i.e., Before Timeout (0x1B; 8 Bytes).....	18
11.3.6	Host Ready (0x1C; 8 Bytes).....	18
11.3.7	Set Even Numbered Package for Recognizing Characters and to Trigger Wake-Up by Tapping Touch Pad (0x1D; 8 Bytes).....	19
11.3.8	Pen Up (Lifting of Stylus) Timeout Offset (0x1E; 8 Bytes)	19
11.3.9	Access the HWRE Firmware Version (0x40; 8 Bytes)	20
11.3.10	Output with Different Code Table (0x41; 8 Bytes).....	20
11.3.11	Software Reset (0x42; 8 Bytes)	21
11.3.12	Abort the Current Inking (0x43; 8 Bytes).....	22
11.3.13	Calibration (0x44; 8 Bytes).....	22
11.3.14	Set Writing Area Location (0x46; 8 Bytes)	23
11.3.15	Set Recognition Mode / Graphic Mode (0x49; 8 Bytes).....	23
11.3.16	Set Power Saving Mode (0x4A; 8 Bytes).....	24
11.3.17	Set A/D Resolution (0x4B; 8 Bytes)	24
11.3.18	Rotate Touch Panel (0x4C; 8 Bytes).....	25
11.3.19	Output PROM/DROM checksum (0xF0; 8 Bytes).....	25
11.4	Responses from ePH1200 Specifications	26
11.4.1	ACK_ERROR (0x00; 8 Bytes).....	26
11.4.2	Inking (Access to Written Input) Coordinates (0x16; 6 Bytes)	26
11.4.3	Touch Panel Button Coordinates (0x17; 6 Bytes; 0xFF is Pen Up Signal).....	27
11.4.4	Recognized Characters Array (0x18; Maximum 25 Bytes; Minimum 6 Bytes)	28
11.4.5	Exit from Power Saving Mode (0x33; 8 Bytes)	28
11.4.6	Initial Power On (0x42; 8 Bytes).....	30
11.4.7	ACK_OK (Carry Out Host Command; 8 Bytes)	30
11.5	Checksum Program.....	31
12	Package LQFP44	32
13	Tape Reel Specification	33

Specification Revision History		
Doc. Version	Revision Description	Date
2.0	ePH1200 initial specification (derived from ePH1100 V2.2)	2005/06/08