



## 1519L 15" LCD Desktop Touchmonitor

The **1519L 15" LCD Desktop Touchmonitor** is a wide-screen display that is easier to use and incorporate into more environments than traditional desktop touchmonitors. It allows extra content on the screen and is well-suited for corporate environment uses such as spreadsheets, publishing, and dual-window applications.

The 1519L is available with a choice of industry-leading Elo touchscreen technologies: zero-bezel Acoustic Pulse Recognition (APR), which senses touch on the display by recognizing the unique pattern of sounds, iTouch zero-bezel surface acoustic wave, standard-bezel IntelliTouch surface acoustic wave, AccuTouch zero-bezel 5-wire resistive, and zero-bezel projected capacitive (PCAP).

Additional applications well-suited to take advantage of the monitor's features include point-of-sale (POS), point-of-information (POI), point-of-service, interactive digital signage, loyalty systems, kiosk information systems, light industrial shop-floor automation and home control.

### Features

- Available with four zero-bezel touchscreen technologies: AccuTouch resistive, APR, iTouch surface acoustic wave and PCAP
- Wide-screen format provides more application space
- Uninterrupted, easy-to-clean, true-flat display area and glass-to-edge design for a sleek stylish look
- Plug and play multi-touch PCAP technology (no drivers needed—Windows® 7 required)
  - Durable glass touch screen senses human touch (eliminates false touches—continues to function even with contaminants or scratches on touch screen)
- Pure glass construction with APR, iTouch, IntelliTouch and PCAP provides superior optical performance
- “Designed for touch” features such as a stable tilt stand
- Space-saving built-in speakers
- User-lockable on-screen display—designed for public access
- Can also be used in portrait mode
- VESA compliance makes wall or arm-mounting possible
- VGA video input
- Screen is resistant to water, dust, grease
- One-time factory calibration for easy deployment and integration with APR and IntelliTouch only
- Headphone jacks

# 1519L 15" LCD Desktop Touchmonitor Specifications

Enclosure Color	Dark gray
Display	Size: 15.6" diagonal; Aspect ratio: 16:9
Useful Screen Area	Horizontal: 13.4" (344 mm); Vertical: 7.6" (194 mm)
Maximum Monitor Dimensions	Width: 15.1" (383 mm); Height: 10.9" (277 mm); Depth: 8.4" (213 mm)
Native (optimal) Resolution	1366 x 768 at 60 Hz
Other Supported Resolutions	1680 x 1050 at 60 Hz; 1600 x 1200 at 60 Hz; 1440 x 900 at 60 Hz; 1366 x 768 at 60 Hz; 1360 x 768 at 60 Hz; 1280 x 1024 at 60 or 75 Hz; 1280 x 960 at 60 Hz; 1280 x 800 at 60 Hz; 1280 x 768 at 65 Hz; 1024 x 768 at 60, 70 or 75 Hz; 832 x 624 at 75 Hz; 800 x 600 at 56, 60 or 72 or 75 Hz; 720 x 400 at 70 Hz; 640 x 480 at 60, 72 or 75 Hz
Colors	16.7 million
Brightness (typical)	LCD panel: 250 nits; Acoustic Pulse Recognition: 225 nits; IntelliTouch: 225 nits; AccuTouch: 200 nits; iTouch: 225 nits; Projected Capacitive: 225 nits
Response Time (typical)	8 msec
Viewing Angle (typical)	Horizontal: $\pm 45^\circ$ or $90^\circ$ total; Vertical: $-20^\circ/+45^\circ$ or $65^\circ$ total
Contrast Ratio (typical)	500:1
Input Video Format	Analog VGA
Input Video Signal Connector	Mini D-Sub 15-Pin VGA type
Input Frequency	Horizontal: 30-83 kHz; Vertical: 50-75 Hz
Power Supply	AC-DC power adapter
Monitor input	Connector: Coaxial power jack (Barrel inner diameter: $6.4 \pm 0.3$ mm. Pin outer diameter: $2.0 + 0.0-0.1$ mm. Barrel depth: $8.8 \pm 0.3$ mm); Voltage Range: 12 V $\pm$ 5%
AC/DC Adapter input	Connector: IEC 60320 C6; Voltage Range: 100-240VAC, 50/60 Hz
Power consumption (typical)	Monitor only, no audio: 15.6 W; Monitor plus AC/DC Adapter at 230V/50 Hz, no audio: 18.4W
Temperature	Operating: 0°C to 40°C (32°F to 104°F); Storage: -50°C to 60°C (-4°F to 122°F)
Humidity (noncondensing)	Operating: 20%-80%; Storage: 10%-90%
Altitude	Operating: 0m-3,658m (12,000 ft.); Storage: 0m-12,192m (40,000 ft.)
Weight	Actual with stand: 11.3 lb (5.1 kg); Actual without stand: 7.5 lb (3.4 kg); Shipping with stand: 16.4 lb (7.4 kg)
Shipping box dimensions (W x D x H)	18.7" (47.5 cm) x 13.8" (35.0 cm) x 8.86" (22.5 cm)
Warranty	3 years
Optional product coverage	Advance Unit Replacement program (North America only)
MTBF	50,000 hours demonstrated
Agency approvals	North America/Worldwide: USA UL, Canada cUL, Mexico NOM, CB; South America: Argentina S-mark; Asia: China CCC, Japan VCCI, Korea KC, Korea KKC, Taiwan BSMI; Elo Declarations: RoHS, China RoHS, WEEE, IMERC, CE
Speakers	Two 2W internal speakers
Audio input connector	3.5mm TRS jack
Audio input signal range	1Vrms maximum stereo signal (standard PC line out)
Headphone output connector	3.5mm TRS jack x 2, wired in parallel
Headphone output signal (for 1KHz signal)	Delivers 90mW of power into a single 32-ohm stereo load
On-screen display (OSD)	Controls: menu, up, down, select, power; Settings: automatic adjustment, contrast, brightness, H/V position, clock, phase, maintain aspect ratio, color temperature, OSD H/V position, OSD timeout, OSD rotation, recall defaults, sharpness, volume, mute; OSD language: English, French, Italian, German, Spanish, Japanese, Traditional Chinese, Simplified Chinese Lockouts: power, user controls
Stand options	Tilt, pivot (landscape/portrait mode)
Mounting options	1. With provided stand (on flat surface or bolted to surface via holes in base) in landscape or portrait mode; 2. 75mm VESA mount
Sealing	Touchscreen sealed to bezel; Touchscreen sealed to LCD
Other features	Security lock receptacle

To find out more about our extensive range of Elo touch solutions, go to [www.elotouch.com](http://www.elotouch.com), or call the office nearest you.

North America	Europe	Asia-Pacific	Latin America
800-ELO-TOUCH	800-ELO-TOUCH	800-ELO-TOUCH	800-ELO-TOUCH
Elo TouchSystems	Elo TouchSystems	Elo TouchSystems	Elo TouchSystems
Tel 1-650-361-4800	Tel +32 (0)16 35 21 00	Tel +81 (45) 478-2161	Tel 786-923-0251
301 Constitution Drive	Fax +32 (0)16 35 21 01	Fax +81 (45) 478-2180	Fax 305-931-0124
Menlo Park, CA 94025-1110	customerservice@elotouch.com	elosales@elotouch.com	www.elotouch.com.ar
		www.tps.co.jp	



Tyco Electronics Corporation and its Affiliates in the TE Touch Solutions business unit of the TE Connectivity Ltd. family of companies (collectively "TE") reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

AccuTouch, Elo (logo), Elo TouchSystems, IntelliTouch, iTouch, TE Connectivity, TE connectivity (logo) and TE (logo) are trademarks of the TE Connectivity Ltd. family of companies.

Copyright 2012 Tyco Electronics Corporation, a TE Connectivity Ltd. Company. All rights reserved. 03/12

