



5500L 55" Interactive Digital Signage (IDS) Touch Display

The Elo Touch Solutions 55-inch 5500L is a large-format canvas for commercial interactive media applications bringing interactivity to digital signage. By combining precision touchscreen technology with a professional-grade, large format LCD panel, the 5500L is rugged enough to last in high traffic, public access environments. With the easy, cable-free, 2-step installation of one of the optional computer modules, the 5500L is a reliable, digital platform that is interoperable with content management servers and supports optimal partitioning of locally cached and network stored content.

Features and Benefits:

- Reduces power consumption and heat output with the thin profile LED-backlight panel
- A choice of three pure-glass touchscreen technologies for visual clarity:
 - Optical for up to 4 touches and gesture support (Windows 7 required)
- IntelliTouch single-touch surface acoustic wave (SAW) touchscreen stands out for consistent reliability
- the seamless, zero-bezel Acoustic Pulse Recognition (APR) for an elegant appearance and touch recognition by finger, prosthetic, stylus, card, or pen
- Built with a durable steel chassis to withstand the rigors of public use over consumer-type displays
- Field-installable, high-performance computer modules in three processing models:
 - ECM1 with the Intel Celeron Dual-Core 2.2GHz
 - ECM2 with the Intel Core 2 Duo 3.0GHz
 - ECM3 with the Intel Core i5 2.5GHz
- Lock-out power and display controls to minimize tampering
 - Built-in speakers expand audio capabilities
 - Mountable in landscape or portrait orientation to suit a variety of design layouts
 - Measure real-time advertising and content effectiveness with interactive feedback



5500L 55" Interactive Digital Signage (IDS) Touch Display

Model	5500L
Active Display Area	47.6" x 26.8" (1209.6 x 680.4mm)
Dimensions*	50.8" x 29.9" x 4.8" (1290.9 x 761.7 x 122.4mm)
Touchscreen technology	IntelliTouch surface acoustic wave; optical multi-touch
LCD Technology	Active matrix TFT LCD with LED backlight
Display Size	54.6" diagonal
On-Screen Display (OSD)	Accessible through switches on the rear, or through the standard Elo OSD control box accessory (sold separately). Controls: Menu, Up, Down, Select; Settings: Brightness, Contrast, Clock, Phase, Auto Adjust, H position, V-position, Maintain Aspect Ratio, Sharpness, Color Temperature, OSD Timeout, OSD Language, Mounting, OSD H-Position, OSD V-Position, Volume, Mute, Recall Defaults, Video Source, Audio Source, ECM MDC; Languages: English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese; Lockouts: OSD, Power
Monitor Diagnostics Control	RS-232 interface or through Elo computer module docking connector
Mounting Options	VESA MIS-F 600x400, Y, 6, 90 mounting provided on rear. Optional stand accessory is available.
Native Resolution	1920x1080
Aspect Ratio	16:9
Preset Video Timings	640x480 60Hz; 720x480 60Hz; 720x576 50Hz; 800x600 56, 60Hz; 1024x768 60Hz; 1280x720 50, 60Hz; 1280x960 60Hz; 1280x1024 60Hz; 1360x768 60Hz (does not scale; image is centered on panel and the remaining active area is filled with black); 1366x768 60Hz; 1440x900 60Hz; 1680x1050 60Hz; 1920x1080 60Hz
Number of Colors	1073.7 million
Brightness (typical)	LCD Panel: 450 nits; IntelliTouch: 405 nits; optical multi-touch: 405 nits
Response Time (gray to gray) (typical)	6.5 msec
Viewing Angle (typical)	Horizontal: ±89° or 178° total; Vertical: ±89° or 178° total
Contrast Ratio (typical)	4000:1
Video Interfaces	Analog VGA on Female DE-15 connector; HDCP-capable HDMI 1.3 on HDMI Type A receptacle connector; Input Video Horizontal Sync frequency range: 31.5 – 80 KHz; Input Video Vertical Sync (frame rate) frequency range: 47-63 Hz
Power	Input power connector: IEC 60320 C14; Input power signal specifications: 100-240VAC 50/60Hz; Power Consumption (Typical): Monitor only: ON, max audio, 100V/60Hz: 145W; SLEEP, 100V/60Hz: 15W; OFF, 100V/60Hz: 3.5W Monitor with ECM1 Computer Module: S0 – ON, max audio, 100% CPU load, 100V/60Hz: 238W; S3 – STANDBY, 100V/60Hz: 17W; S5 – OFF, 100V/60Hz: 13.2W Monitor with ECM2 Computer Module: ON, max audio, 100% CPU load, 100V/60Hz (S0): 268W; S3 – STANDBY, 100V/60Hz: 17W; S5 – OFF, 100V/60Hz: 13.2W
Audio	Internal speakers: a pair of 10W stereo speakers; Input audio connector: 3.5mm TRS jack; Input audio signal range: 1Vrms max stereo signal (standard PC line out) ; Headphone output connector: 3.5mm TRS jack; Headphone output signal (at 1KHz): delivers 90mW of power into a 32-ohm stereo load
Weight	Unpackaged: Weight without Computer Module: 88.8lb (40.3Kg); Weight with Computer Module: 94.6lb (42.9Kg); Packaged (Computer Module ships separately); Weight: 119.7lb (54.3Kg)
Shipping Dimensions	14.2" x 51" x 38.2" (36 x 145 x 97 cm)
Temperature	Operating: 32°F to 95°F (0° C to 35° C); Storage: -4°F to 122°F (-20° C to 50° C)
Humidity (non-condensing)	Operating: 20%-80%; Storage: 10%-90%
Regulatory approvals and declarations	Argentina S-mark; Australia C-Tick; Canada cUL, IC; China CCC; Europe CE; Japan VCCI; Korea KC; Mexico NOM; Russia & CIS GOST; Taiwan BSMI; United States UL, FCC; International CB
Warranty	3 years
MTBF	50,000 hours demonstrated

*See dimensional drawings for details.

To find out more about our extensive range of Elo touch solutions, go to www.elotouch.com, or call the office nearest you.

North America	800-ELO-TOUCH	Europe	Asia-Pacific	Latin America
Elo Touch Solutions	Tel 1-650-361-4800	Tel +32 (0)16 35 21 00	Tel +81 (45) 478-2161	Tel 786-923-0251
301 Constitution Drive	Fax 1-650-361-4722	Fax +32 (0)16 35 21 01	Fax +81 (45) 478-2180	Fax 305-931-0124
Menlo Park, CA 94025-1110	customerservice@elotouch.com	elosales@elotouch.com	www.tps.co.jp	www.elotouch.com.ar

Elo Touch Solutions, Inc. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo (logo), Elo Touch Solutions and IntelliTouch are trademarks of Elo Touch Solutions, Inc.
Copyright 2012 Elo Touch Solutions, Inc. All rights reserved. 10/12

www.elotouch.com

