

975 ALTA-GLAS P

SERIES *Impregnated Fiberglass Sleeving*



DESCRIPTION

- Custom braided fiberglass sleeving
- Heat-treated and impregnated with a high temperature binder
- UL Recognized/VW-1
- Colors: Black or Natural

FEATURES

- Designed specifically for applications where temperatures as high as 500°C may be encountered
- Impregnation minimizes fraying
- Maintains a round cross section
- Expands slightly providing some ease of installation
- Flexibility allows for formation over tight radii in relatively close spacing
- Available in standard wall thickness and can be made with a heavier wall for applications calling for ultimate protection

APPLICATIONS

- Often used over wires as durable, high temperature protection
- Can be used as primary insulation over low voltage applications such as leads on some appliances and secondary insulation over primary extruded plastic and rubber insulated wire
- Can be used as a high temperature gasketing material

DIMENSIONS

PART NUMBERS (COLOR: BLACK)	COMMON SIZES	I.D. NOMINAL	
		INCH	(MM)
97520010	10	.106	(2.69)
97520009	9	.118	(2.99)
97520008	8	.133	(3.38)
97520007	7	.148	(3.76)
97520006	6	.166	(4.22)
97520005	5	.186	(4.72)
97520004	4	.208	(5.28)
97520003	3	.234	(5.94)
97520002	2	.263	(6.68)
97520001	1	.294	(7.47)
97520000	0	.330	(8.38)
97520375	3/8"	.375	(9.52)
97520500	1/2"	.500	(12.70)
97520625	5/8"	.625	(15.87)

TESTING

PROPERTIES

Tensile Strength @ 72°F
Tensile Strength @ 700°F
Elongation
Specific Gravity
Expansion Coefficient per °F
Specific Heat @ 72°F
Flammability (UL 224)
Operating Temperature

PERFORMANCE

500,000 psi
380,000 psi
4.8%
2.54
2.8×10^{-6}
0.197
VW-1
930°F

The information provided to the left represents average values and is believed to be reliable. Alta Technologies, Inc. makes no warranties as to its accuracy and disclaims any liability in connection with its use. It is provided for general use only and should not be incorporated into any specific specifications.



ALTA TECHNOLOGIES, INC.

P.O. Box 100, Pennington, NJ 08534 | www.altatechinc.com | E: info@altatechinc.com | P: 609-538-9500 | F: 609-538-9501