




STANDARD SPECIFICATIONS


Parameter	Condition	Minimum	Typical	Maximum
Center Frequency (MHz):	-	-	868.000	-
Passband Width (MHz):	-	-	±2.00	-
Insertion Loss (dB):	866.0MHz - 870.0MHz	-	3.00	4.50
Passband Ripple (dB):	866.0MHz - 870.0MHz	-	1.20	2.00
Attenuation (dB):	Fc-400.0MHz to Fo-40.8MHz	40.00	45.00	-
	Fo+50.0MHz to Fo+400.0MHz	40.00	45.00	-
Operating Temperature Range (°C):	-	-10	25	65
Storage Temperature Range (°C):	-	-40	25	85
Input Power (in Passband)(dBm):	-	-	-	10.0
DC Voltage (Vdc):	-	-	-	12.0
Termination Source Impedance (Ohms):	-	-	50	-
Termination Load Impedance (Ohms):	-	-	50	-

Comments: Unless otherwise specified, all of the above specifications are under the following conditions:
Operating Temperature = -10°C to +65°C

MECHANICAL DIMENSIONS




Pin	Function
1	Ground
2	Input
3-5	Ground
6	Output
7-8	Ground



ALL DIMENSIONS
IN MILLIMETERS

MATCHING NETWORK DIAGRAM



MARKING GUIDE

Line 1: ABFF
Line 2: 041A



Part Number: ABFF041A

3545-B Cadillac Avenue • Costa Mesa, CA 92626-1401 • (714) 918-4752 • Fax (714) 918-4760