


STANDARD SPECIFICATIONS

Parameter	Condition	Minimum	Typical	Maximum
Center Frequency (MHz):	-	-	914.000	-
Insertion Loss (dB):	913MHz - 915MHz	-	-	4.50
Passband Ripple (dB):	913MHz - 915MHz	-	-	2.00
Ultimate Attenuation (dB):	Fo-20MHz to Fo-23MHz	30.00	-	-
	Fo-40MHz to Fo-45MHz	45.00	-	-
	Fo+20MHz to Fo+23MHz	20.00	-	-
	Fo+40MHz to Fo+45MHz	35.00	-	-
Operating Temperature Range (°C):	-	-10	25	+50
Storage Temperature Range (°C):	-	-40	25	+85
DC Voltage (Vdc):	-	-	-	0.0
Input Power (in Passband)(dBm):	-	-	-	5.0
Termination Source Impedance (Ohms):	-	-	50	-
Termination Load Impedance (Ohms):	-	-	50	-

Comments: Unless otherwise specified, all of the above specifications are under the following conditions:
 Operating Temperature = -10°C to +50°C


MECHANICAL DIMENSIONS



Pin	Function
1	Ground
2	Input
3-4	Ground
5	Output
6	Ground

ALL DIMENSIONS
IN MILLIMETERS

CONNECTION DIAGRAM



MARKING GUIDE

(Line #1) **ABFF**
 (Line #2) **048C**



Part Number: ABFF048C

3545-B Cadillac Avenue • Costa Mesa, CA 92626-1401 • (714) 918-4752 • Fax (714) 918-4760