




STANDARD SPECIFICATIONS


Parameter	Condition	Minimum	Typical	Maximum
Center Frequency (MHz):	-	-	458.00	-
Passband Width (MHz):	-	-	±2.00	-
Insertion Loss (dB):	456MHz - 460MHz	-	3.20	4.80
Passband Ripple (dB):	456MHz - 460MHz	-	1.00	2.00
Absolute Attenuation (dB):	DC to Fc-20MHz	35.00	45.00	-
	Fc+25MHz to Fc+200MHz.	42.00	52.00	-
Operating Temperature Range (°C):	-	-10	25	65
Storage Temperature Range (°C):	-	-40	25	85
Input Power (in Passband)(dBm):	-	-	-	0.0
DC Voltage (Vdc):	-	-	-	10.0
Termination Source Impedance (Ohms):	-	-	50	-
Termination Load Impedance (Ohms):	-	-	50	-

Comments: Unless otherwise specified, all of the above specifications are under the following conditions:
Operating Temperature = -10°C to +65°C

MECHANICAL DIMENSIONS




Pin	Function
1	Ground
2	Input
3-4	Ground
5	Output
6	Ground



ALL DIMENSIONS
IN MILLIMETERS

MATCHING NETWORK DIAGRAM



MARKING GUIDE

Line 1: ABFF
Line 2: 04AA

NOTE: RoHS Compliant (Pb-free)



Part Number: ABFF04AA

3545-B Cadillac Avenue • Costa Mesa, CA 92626-1401 • (714) 918-4752 • Fax (714) 918-4760