



5300 Beethoven Street, Los Angeles, CA 90066
 TEL: (310)306-5556 • FAX: (310)577-9887
 WEB: www.ophirrf.com • E-MAIL: sales@ophirrf.com

MODEL 5303130
1.5 - 6.0 GHz
0.5 WATTS
LINEAR POWER RF AMPLIFIER

**Solid State
 Band-specific High
 Power RF Amplifier**

The 5303130 is a 0.5 Watt broadband amplifier that covers the 1.5 - 6.0 GHz frequency range. This small and lightweight amplifier utilizes Class A linear power devices that provide an excellent 3rd order intercept point, high gain, and a wide dynamic range.

Due to robust engineering and employment of the most advanced devices and components, this amplifier achieves high efficiency operation with proven reliability.

The 5303130 is designed as a wide-band driver for various applications.

	Parameter	Specification @ 25 °C
<u>Electrical</u>		
1	Frequency Range	1.5 – 6.0 GHz
2	Saturated Output Power	0.5 Watts typical
3	Small Signal Gain	+26 dB min
4	Gain Flatness	± 2.5 dB max
5	Power Flatness	± 1.5 dB max
6	IP ₃	+35 dBm typical
7	Input VSWR	2:1 max
8	Harmonics	-20 dBc typical @ 0.5 Watts
9	Spurious Signals	< -60 dBc typical @ 0.5 Watts
10	Input/Output Impedance	50 Ohms nominal
11	Noise Figure	8 dB nominal
12	DC Input Current	1.5 Amps max
13	DC Input	20 - 36 Vdc
14	RF Input for rated power	0 dBm nominal
15	Maximum RF input	+3 dBm max
16	Class of Operation	A
<u>Mechanical</u>		
17	Dimensions	3.4" x 2.2" x 0.7"
18	Weight	3.5 lb. max
19	Connectors	SMA Female
20	Grounding	Chassis
21	Cooling	Heatsink and adequate airflow
<u>Environmental</u>		
22	Operating Temperature	0° C to +50° C
23	Operating Humidity	95% Non-condensing
24	Operating Altitude	Up to 10,000' Above Sea Level
25	Shock and Vibration	Normal truck transportation

Specifications subject to change without notice

