



5300 Beethoven Street, Los Angeles, CA 90066  
 TEL: (310)306-5556 • FAX: (310)821-7413  
 WEB: www.ophirrf.com • E-MAIL: sales@ophirrf.com

**MODEL 4044**  
**2 - 30 MHz**  
**1800 WATTS**  
**LINEAR POWER RF AMPLIFIER**

**Solid State  
 Band-Specific High  
 Power RF Amplifier**

The 4044 is a 1800 Watt band-specific amplifier that covers the 2 – 30 MHz frequency range. This small and lightweight amplifier utilizes Class A/AB linear power devices that provide an excellent 3<sup>rd</sup> order intercept point, high gain, and a wide dynamic range.

Due to robust engineering and employment of the most advanced devices and components, this amplifier achieves high efficiency operation with proven reliability. Like all OPHIR<sub>RF</sub> amplifiers, the 4044 comes with an extended multiyear warranty.



**FE Model Shown**

	<u>Parameter</u>	<u>Specification @ 25° C</u>
<b><u>Electrical</u></b>		
1	Frequency Range	2 – 30 MHz
2	Saturated Output Power	1800 Watts typical
3	Power Output @ 1dB Comp.	1100 Watts min
4	Small Signal Gain	+63 dB min
5	Small Signal Gain Flatness	± 2.0 dB max
6	IP <sub>3</sub>	+66 dBm
7	Input VSWR	2:1 max
8	Harmonics	-15 dBc typical @ 1100 Watts
9	Spurious Signals	-60 dBc typical @ 1100 Watts
10	Input/Output Impedance	50 Ohms nominal
11	AC Input Power	5500 Watts max
12	AC Input	208 ± 10% VAC, single phase
13	Nominal RF Input	0 dBm
14	RF Input Overdrive	+13 dBm max
15	RF Input Signal Format	CW/AM/FM/PM
16	Class of Operation	AB
<b><u>Mechanical</u></b>		
17	Dimensions* (W x H x D)	22.5" x 31" x 26"
18	Weight*	300 lbs. max
19	RF Connectors	Type-N
20	Grounding	Chassis
21	Cooling	Internal Forced Air
<b><u>Environmental</u></b>		
22	Operating Temperature	0° C to +50° C
23	Operating Humidity	95% Non-condensing
24	Operating Altitude	Up to 10,000' Above Sea Level
25	Shock and Vibration	Normal Truck Transport

\* Dimensions and weight include cabinet enclosure.

Specifications subject to change without notice.

**CIRCUIT PROTECTIONS**

- ◇ Thermal Shutdown
- ◇ Over Voltage
- ◇ High VSWR Alarm
- ◇ RF Input Overdrive Protection

**ORDERING MODELS**

- ◇ RE - Rear panel RF connectors
- ◇ FE - Front panel RF connectors
- ◇ RT - RE model with Ethernet
- ◇ FT - FE model with Ethernet

Approved By: \_\_\_\_\_ Date: \_\_\_\_\_