



5300 Beethoven Street, Los Angeles, CA 90066
 TEL: (310)306-5556 • FAX: (310)821-7413
 WEB: www.ophirrf.com • E-MAIL: sales@ophirrf.com

MODEL 4007
400 - 450 MHz
1000 WATTS
LINEAR POWER RF AMPLIFIER

**Solid State
 Band-specific High
 Power RF Amplifier**

The 4007 is a 1000 Watt band-specific amplifier that covers the 400 – 450 MHz frequency range. This small and lightweight amplifier utilizes Class A/AB linear power devices that provide an excellent 3rd order intercept point, high gain, and a wide dynamic range.

Due to robust engineering and employment of the most advanced devices and components, this amplifier achieves high efficiency operation with proven reliability. Like all OPHIR_{RF} amplifiers, the 4007 comes with an extended multiyear warranty.

| | <u>Parameter</u> | <u>Specification @ 25° C</u> |
|-----------------------------|----------------------------|---|
| <u>Electrical</u> | | |
| 1 | Frequency Range | 400 – 450 MHz |
| 2 | Saturated Output Power | 1000 Watts typical |
| 3 | Power Output @ 1dB Comp. | 600 Watts min |
| 4 | Small Signal Gain | +62 dB min |
| 5 | Small Signal Gain Flatness | ± 1.5dB max |
| 6 | IP ₃ | +64 dBm typical |
| 7 | Input VSWR | 2:1 max |
| 8 | Harmonics | -20 dBc typical @ 600 Watts |
| 9 | Spurious Signals | < -60 dBc typical @ 600 Watts |
| 10 | Input/Output Impedance | 50 Ohms nominal |
| 11 | AC Input Power | 3300 Watts max |
| 12 | AC Input | 180 – 240 VAC, single phase or 3 phases |
| 13 | RF Input | 0 dBm typical |
| 14 | RF Input Signal Format | CW/AM/FM/PM/Pulse |
| 15 | Class of Operation | AB |
| <u>Mechanical</u> | | |
| 16 | Dimensions | 19" x 8.75" x 20" |
| 17 | Weight | 85 lb. max |
| 18 | Connectors | Type-N |
| 19 | Grounding | Chassis |
| 20 | Cooling | Internal Forced Air |
| <u>Environmental</u> | | |
| 21 | Operating Temperature | 0° C to +50° C |
| 22 | Operating Humidity | 95% Non-condensing |
| 23 | Operating Altitude | Up to 10,000' Above Sea Level |
| 24 | Shock and Vibration | Normal Truck Transport |

Specifications subject to change without notice.

CIRCUIT INDICATIONS

- ◇ Forward Power
- ◇ Reflected power
- ◇ VSWR Fault
- ◇ Temp Fault
- ◇ Gain Setting (VVA) percentage

CIRCUIT PROTECTIONS

- ◇ Thermal Overload
- ◇ Over Current
- ◇ Over Voltage

ORDERING MODELS

- ◇ RE - R model with Ethernet, IEEE488 and RS232
- ◇ FE - F model with Ethernet, IEEE488 and RS232



FE Model Shown