

GT SERIES

GTTM 051



Features:

- Huge storage capacity up to 1TB
- Sustain data rates of 40 MB/sec with FireWire (IEEE 1394a/iLink)
- FireWire connectivity is hot pluggable and allows 63 devices daisy chained
- Fast 7,200 RPM, ATA/100 Seagate drives with up to an 8MB cache
- Scratch resistant black powder-coated aluminum chassis offers excellent heat transfer properties
- Stainless steel, fan cooled enclosure is rack-mountable
- Engineered for Professional Audio and Video Production
- Comes complete with Glyph's 24-hour advance replacement warranty along with outstanding technical support at no additional charge.

Make content more portable, and expansion easy

The GT 051 can be used as a single solution or in collaboration with other GT Series enclosures to easily shuttle content between locations using the GT Key drive. The 7200 RPM GT Key (FW400 or FW800 version) works across all GT Series enclosures using Integrity™, Glyph's proprietary hot-swap technology. Integrity™ is an advanced FireWire hot-swap interface that provides greater reliability than existing hybrid ATA-to-FireWire products. Older FireWire 400 GT Keys are forward-compatible with the FireWire 800 GT 051, and FireWire 800 GT Keys are backward-compatible with all GT Series FireWire 400 enclosures. Glyph's GT 051 comes standard with a three-year warranty, while GT Keys carry an additional overnight advance replacement in the first year.

GT 051 FW400 Specifications

- Interface: Two IEEE 1394a/iLink (FireWire 400) connectors
- Dimensions: H 1.72" x W 8.61" x D 9.47"
- Power supply: Universal 100-240v, 50-60 Hz
- Weight (lbs/kg): 5.8 lbs/2.6 kg (fully loaded), 2.9 lbs/1.3 kg (empty)
- Compatibility: Mac OS 8.6/9.x/10.x, Windows 98SE/2000/ME/XP, Linux
- Includes: 2 meter FireWire cable, power cable
- Warranty: 3 years

GT Key FW400 Specifications

- Capacity: 80, 160, 250, 320, 400, 500, 750GB
- Rotational speed: 7,200 RPM
- Bridging: Oxford 911 chip on Glyph's own bridge board
- Buffer size (cache): 2MB (80GB), 8MB (160GB - 750GB)
- Average seek time (read): 8 msec
- Max external transfer rate: 400 Mb/sec (50 MB/sec)
- Dimensions: H 1.1" x W 4.6" x D 9.4"
- Weight (lbs/kg): 2.9 lbs / 1.3 kg
- Power supply: Gets power from enclosure
- Operating Temperature (C/F): 41 - 122/5 - 50
- Warranty: 3 years, Overnight advance replacement warranty in the first year



Shown with optional rack ears

