

GT SERIES

GTTM 103



Features

- Capacity of 3TB with 1TB drives
- Sustain data rates of 40 MB/sec with FireWire (IEEE 1394a/iLink)
- FireWire connectivity is hot pluggable and allows 63 devices daisy chained
- Fast 7,200 RPM, ATA/100 Seagate drives with up to an 8MB cache
- Scratch resistant black powder-coated aluminum chassis offers excellent heat transfer properties
- FireWire Port accessible on the front panel
- Dual internal 70w power supplies, and dual whisper quiet fans
- Comes complete with Glyph's 24-hour advance replacement warranty along with outstanding technical support at no additional charge.

Custom Configure Three Drives in a Single Space Rack with the GT 103.

Specifically designed for applications requiring multiple drives, the GT 103 can be configured with three FireWire hot-swap GT Key drives of any capacity. Using Integrity™, Glyph's proprietary hot-swap technology, you can easily shuttle content to other GT Series enclosures with the 7,200 RPM GT Key. Integrity™ is an advanced FireWire hot-swap interface that provides greater reliability than existing hybrid ATA-to-FireWire products. Older FireWire 400 GT Keys are forward-compatible with the FireWire 800 GT 103, and FireWire 800 GT Keys are backward-compatible with all GT Series FireWire 400 enclosures. Glyph's GT 103 comes standard with a three-year warranty, while GT Keys carry an additional overnight advance replacement warranty in the first year.

GT 103 FW400 Specifications

- Interface: Three IEEE 1394a/iLink (FireWire 400) connectors
- Dimensions: H 1.7" x W 19" x D 16"
- Power supply: Universal 100-240v, 50-60 Hz
- Weight (lbs/kg): 16 lbs/7 kg (fully loaded), 11.5 lbs/5.2 kg (empty)
- Compatibility: Mac OS 8.6/9.x/10.x, Windows 98SE/2000/ME/XP, Linux
- Includes: 2 meter FireWire cable, power cable, rack screws, downloadable manual
- Warranty: 3 years

GT Key FW400 Specifications

- Capacity: 80, 160, 250, 320, 400, 500, 750GB
- Rotational speed: 7,200 RPM
- Bridging: Oxford 911 chip on Glyph's own bridge board
- Buffer size (cache): 2MB (80GB), 8MB (160GB - 750GB)
- Average seek time (read): 8 msec
- Max external transfer rate: 400 Mb/sec (50 MB/sec)
- Dimensions: H 1.1" x W 4.6" x D 9.4"
- Weight (lbs/kg): 2.9 lbs / 1.3 kg
- Power supply: Gets power from enclosure
- Operating Temperature (C/F): 41 - 122/5 - 50
- Warranty: 3 years, Overnight advance replacement warranty in the first year

