

LME-1738 Specification



17"

Value Series

CCTV LCD Monitor (Foldable Stand)

Features

- 3D Comb Filter ■
- De-Interlace ■
- Foldable Stand Design ■
- Unique Alarm Video Swap ■
- Looping BNC Connectors (Input & Output) ■
- System ID Remote Controller with 999 Codes ■

Display

Aspect Ratio 4 : 3
 Resolution 1280 x 1024
 Pixel Pitch 0.264 (H) x 0.264 (V)
 Contrast Ratio 800 : 1
 Brightness 300 cd/m²
 Viewing Angle 160 (H) / 160 (V)
 Response Time Tr+Tf=5 ms
 Video Color System NTSC / PAL Auto Scanning
 Scan Frequency H:30~80KHz, V:50~75Hz

Operation Interface

OSD Language (12):
 English, French, Spanish, Italian, German, Portuguese, Polish,
 Czech, Dutch, Magyar, Chinese-Simplified, Chinese-Traditional

Input Connector

D-Sub x 1
 Looping BNC Video x 2
 S-Video x 1
 RCA Audio x 2sets (L+R=1set)
 PC Audio Ø 3.5 Jack x 1
 Alarm Trigger Signal x 1
 Power AC x 1
 Power DC x 1

Output Connector

Looping BNC Video x 2
 RCA Audio x 2 sets (L+R=1set)
 Power DC x 1 (DC12V / 1A)

Mechanical & Electrical Design

Alarm Video Swap
 3D Comb Filter (PAL & NTSC)
 De-Interlace
 Scan Mode (Under & Over Scan)
 Freeze Frame
 Backlight Adjustment
 Power Failure Auto Recovery
 Auto Moving
 Key Lock & Source Lock
 System ID Remote Control (999 codes)
 Metal Stand, Plastic Front Bezel and Plastic Cabinet
 VESA Mount Compatible (100 x 100 mm)
 Speaker 1.5W x 2
 Power AC100~240V, 50/60Hz
 Power Consumption 60W (Max)

Optional

Glass Protection / Rack Mount

Product design and specification are subject to change without notice.

LME-1938 Specification



19" Value Series CCTV LCD Monitor (Foldable Stand)

Features

- 3D Comb Filter ■
- De-Interlace ■
- Foldable Stand Design ■
- Unique Alarm Video Swap ■
- Looping BNC Connectors (Input & Output) ■
- System ID Remote Controller with 999 Codes ■

Display

- Aspect Ratio 4 : 3
- Resolution 1280 x 1024
- Pixel Pitch 0.294 (H) x 0.294 (V)
- Contrast Ratio 1000 : 1
- Brightness 300 cd/m²
- Viewing Angle 170 (H) / 160 (V)
- Response Time Tr+Tf=5 ms
- Video Color System NTSC / PAL Auto Scanning
- Scan Frequency H:30~80KHz, V:50~75Hz

Operation Interface

- OSD Language (12):
- English, French, Spanish, Italian, German, Portuguese, Polish, Czech, Dutch, Magyar, Chinese-Simplified, Chinese-Traditional

Input Connector

- D-Sub x 1
- Looping BNC Video x 2
- S-Video x 1
- RCA Audio x 2sets (L+R=1set)
- PC Audio Ø 3.5 Jack x 1
- Alarm Trigger Signal x 1
- Power AC x 1
- Power DC x 1

Output Connector

- Looping BNC Video x 2
- RCA Audio x 2 sets (L+R=1set)
- Power DC x 1 (DC12V / 1A)

Mechanical & Electrical Design

- Alarm Video Swap
- 3D Comb Filter (PAL & NTSC)
- De-Interlace
- Scan Mode (Under & Over Scan)
- Freeze Frame
- Backlight Adjustment
- Power Failure Auto Recovery
- Auto Moving
- Key Lock & Source Lock
- System ID Remote Control (999 codes)
- Metal Stand, Plastic Front Bezel and Plastic Cabinet
- VESA Mount Compatible (100 x 100 mm)
- Speaker 1.5W x 2
- Power AC100~240V, 50/60Hz
- Power Consumption 65W (Max)

Optional

- Glass Protection / Rack Mount

Product design and specification are subject to change without notice.