

# LME-1736 Specification



## 17" Premium Series CCTV LCD Monitor

### Features

3D Comb Filter ■

De-Interlace ■

Intelligent Vanish PIP ■

Scrolling Text Generator ■

Looping BNC Connectors (Input & Output) ■

Full metal type, high brightness type, ■

and touch panel type are available

■ Full Metal



■ High Brightness



■ Touch Panel



### Display

Aspect Ratio 4 : 3

Resolution 1280 x 1024

Pixel Pitch 0.264 (H) x 0.264 (V)

Contrast Ratio 800 : 1

Brightness 300 cd/m<sup>2</sup>

Viewing Angle 160 (H) / 160 (V)

Response Time Tr+Tf=5 ms

Video Color System NTSC / PAL Auto Scanning

Scan Frequency H:31~80KHz, V:50~75Hz

### Operation Interface

OSD Language (12):

English, French, Spanish, Italian, German, Portuguese, Polish, Czech, Dutch, Magyar, Chinese-Simplified, Chinese-Traditional

### Input Connector

DVI-I x 1

Looping BNC Video x 2

S-Video x 1

RCA Audio x 2sets (L+R=1set)

PC Audio Ø 3.5 Jack x 1

Alarm Trigger Signal x 1

Power AC x 1

Power DC x 1

### Output Connector

Looping BNC Video x 2

RCA Audio x 2sets (L+R=1set)

Power DC x 1 (DC12V / 1A)

### Mechanical & Electrical Design

Vanishing PIP

POP (Any Size)

Scrolling Text Generator

3D Comb Filter (PAL & NTSC)

De-Interlace

Scan Mode (Under & Over Scan)

Freeze Frame

Backlight Adjustment

Power Failure Auto Recovery

Auto Moving

Key Lock & Source Lock

System ID Remote Control (999 codes)

Metal Stand, Metal Cabinet and Plastic Front Bezel

VESA Mount Compatible (100 x 100 mm)

Speaker 1.5W x 2

Power AC100~240V, 50/60Hz

Power Consumption 60W (Max)

### Optional

Glass Protection / Rack Mount

Product design and specification are subject to change without notice.

# LME-1936 Specification



## 19" Premium Series CCTV LCD Monitor

### Features

3D Comb Filter ■

De-Interlace ■

Intelligent Vanish PIP ■

Scrolling Text Generator ■

Looping BNC Connectors (Input & Output) ■

Full metal type, high brightness type, ■

and touch panel type are available

■ Full Metal



■ High Brightness



■ Touch Panel



### Display

Aspect Ratio 4 : 3

Resolution 1280 x 1024

Pixel Pitch 0.294 (H) x 0.294 (V)

Contrast Ratio 1000 : 1

Brightness 300 cd/m<sup>2</sup>

Viewing Angle 170 (H) / 160 (V)

Response Time Tr+Tf=5 ms

Video Color System NTSC / PAL Auto Scanning

Scan Frequency H:30~80KHz, V:50~75Hz

### Operation Interface

OSD Language (12):

English, French, Spanish, Italian, German, Portuguese, Polish, Czech, Dutch, Magyar, Chinese-Simplified, Chinese-Traditional

### Input Connector

DVI-I x 1

Looping BNC Video x 2

S-Video x 1

RCA Audio x 2sets (L+R=1set)

PC Audio Ø 3.5 Jack x 1

Alarm Trigger Signal x 1

Power AC x 1

Power DC x 1

### Output Connector

Looping BNC Video x 2

RCA Audio x 2sets (L+R=1set)

Power DC x 1 (DC12V / 1A)

### Mechanical & Electrical Design

Vanishing PIP

POP (Any Size)

Scrolling Text Generator

3D Comb Filter (PAL & NTSC)

De-Interlace

Scan Mode (Under & Over Scan)

Freeze Frame

Backlight Adjustment

Power Failure Auto Recovery

Auto Moving

Key Lock & Source Lock

System ID Remote Control (999 codes)

Metal Stand, Metal Cabinet and Plastic Front Bezel

VESA Mount Compatible (100 x 100 mm)

Speaker 1.5W x 2

Power AC100~240V, 50/60Hz

Power Consumption 65W (Max)

### Optional

Glass Protection / Rack Mount

Product design and specification are subject to change without notice.