

LME-3236 Specification



32" HD CCTV LCD Monitor

Features

- 3D Comb Filter ■
- De-Interlace ■
- Looping BNC Connectors (Input & Output) ■
- System ID Remote Controller with 999 Codes ■

Display

- Aspect Ratio 16 : 9
- Resolution 1366 x 768 (HD)
- Pixel Pitch 0.51075 (H) x 0.51075 (V)
- Contrast Ratio 1500 : 1
- Brightness 500 cd/m²
- Viewing Angle 178 (H) / 178 (V)
- Response Time Tr+Tf=8 ms
- Video Color System NTSC / PAL Auto Scanning
- Scan Frequency H:30~80KHz, V:56~75Hz

Operation Interface

- OSD Language (12):
- English, French, Spanish, Italian, German, Portuguese, Polish, Czech, Dutch, Magyar, Chinese-Simplified, Chinese-Traditional

Input Connector

- HDMI x 1
- Looping BNC Video x 2
- S-Video x 1
- Audio x 1 set (L+R=1 set)
- YCbCR x 1

Output Connector

- Looping BNC Video x 2
- S-Video x 1
- Audio x 1 set (L+R=1 set)

Mechanical & Electrical Design

- 3D Comb Filter (PAL & NTSC)
- De-Interlace
- Scan Mode (Under & Over Scan)
- Freeze Frame
- Backlight Adjustment
- Power Failure Auto Recovery
- Auto Moving
- Key Lock & Source Lock
- System ID Remote Control (999 codes)
- VESA Mount Compatible (200 x 200 mm)
- Speaker 2W x 2
- Power AC100~240V, 50/60Hz
- Power Consumption 190W (Max)

Optional

- Stand / Wall Mount

Product design and specification are subject to change without notice.

LME-4236 Specification



42" Full HD CCTV LCD Monitor

Features

- 3D Comb Filter ■
- De-Interlace ■
- Looping BNC Connectors (Input & Output) ■
- System ID Remote Controller with 999 Codes ■

Display

- Aspect Ratio 16 : 9
- Resolution 1920 x 1080P (Full HD)
- Pixel Pitch 0.4845 (H) x 0.4845 (V)
- Contrast Ratio 1400 : 1
- Brightness 500 cd/m²
- Viewing Angle 178 (H) / 178 (V)
- Response Time Tr+Tf=5 ms
- Video Color System NTSC / PAL Auto Scanning
- Scan Frequency H:30~80KHz, V:56~75Hz

Operation Interface

- OSD Language (12):
- English, French, Spanish, Italian, German, Portuguese, Polish, Czech, Dutch, Magyar, Chinese-Simplified, Chinese-Traditional

Input Connector

- HDMI x 1
- Looping BNC Video x 2
- S-Video x 1
- Audio x 1 set (L+R=1set)
- YCbCR x 1

Output Connector

- Looping BNC Video x 2
- S-Video x 1
- Audio x 1 set (L+R=1set)

Mechanical & Electrical Design

- 3D Comb Filter (PAL & NTSC)
- De-Interlace
- Scan Mode (Under & Over Scan)
- Freeze Frame
- Backlight Adjustment
- Power Failure Auto Recovery
- Auto Moving
- Key Lock & Source Lock
- System ID Remote Control (999 codes)
- VESA Mount Compatible (200 x 200 mm)
- Speaker 2W x 2
- Power AC100~240V, 50/60Hz
- Power Consumption 250W (Max)

Optional

- Stand / Wall Mount

Product design and specification are subject to change without notice.