




**Output Plug
and Polarity are
Dependent on
Customer
Requirements**

General Specifications

- Input: 100~240Vac/ 47~63Hz
- Output: +3VDC/0~3000mA Regulated
- DC Cord: Atleast 6FT, 22AWG
- Operating/Storage Temperature: 0°C ~+40°C/ -20°C~+70°C
- Operating/Storage Humidity: 10%~95%RH/10%~95%RH
- M.T.B.F.: 50,000 Hrs. Minimum (25°C Ambient Temp., Full Load)
- Approvals: UL/ CUL/ FCC/ LPS/ TUV/ CE/ WEEE/ ROHS/ I V
- Meets Energy Efficiency Level IV Standards
- Protection: Over Voltage/Short Circuit
- Packaged Unit Weight: .25 Lbs
- Carton Quantity: 100 Pcs

REV	DESCRIPTION	DATE	BY
A			
B			

ITEM NUMBER	S-3V0-3A0-I2-30	PART TITLE	Energy Efficient 3VDC/ 3.0A Universal Input Power Supply
PART NUMBER	SA-033A0IV-2W	 CONDOR ELECTRONICS, INC. T: 408-745-7141 F: 408-745-0439 780 Montague Expy. Ste. 406 San Jose, CA 95131 USA sales@condorelectronics.net	
DATE	10.28.10		
APPROVAL	EB		
UNIT	mm		
REV	Ø		