





Output Plug
and Polarity are
Dependent on
Customer
Requirements

General Specifications

- Input: 100~240Vac/ 47~63Hz
- Output: +12VDC/0~1000mA Regulated
- DC Cord: 8FT, 22AWG
- Operating/Storage Temperature: 0°C ~+40°C/ -20°C~+70°C
- Operating/Storage Humidity: 10%~90%RH/10%~90%RH
- M.T.B.F.: 50,000 Hrs. Minimum (25°C Ambient Temp., Full Load)
- Approvals: UL/ CUL/ FCC/ LPS/ WEEE/ ROHS/ IV
- Meets Energy Efficiency Level IV Standards
- Protection: Over Voltage/Short Circuit
- Packaged Unit Weight: 0.36 Lbs
- Carton Quantity: 60 pcs

Inner White Box Dimensions:



REV	DESCRIPTION	DATE	BY
A			
B			

ITEM NUMBER	S-12V0-1A0-UDG30	PART TITLE	Energy Efficient 12VDC/ 1.5A Universal Input Power Supply
PART NUMBER	SA-121A0DG	 CONDOR ELECTRONICS, INC. T: 408-745-7141 F: 408-745-0439 780 Montague Expy. Ste. 406 San Jose, CA 95131 USA sales@condorelectronics.net	
DATE	12.09.2013		
APPROVAL	CB		
UNIT	mm		
REV	Ø		