





General Specifications

- Input: 100~240Vac/ 47~63Hz
- Output: +12VDC/0~12500mA Regulated
- DC Cord: 5 FT, 16 AWG
- Operating/Storage Temperature: 0°C ~+40°C/ -20°C~+80°C
- Operating/Storage Humidity: 20%~80%RH/ 10%~90%RH
- M.T.B.F.: 300,000 Hrs. Minimum (25°C Ambient Temp., Full Load)
- Approvals: UL/ CUL/ FCC/ PSE/ BSMI/ TUV/ RCM/ CE/ WEEE/ ROHS/ V
- Meets Energy Efficiency Level V Standards
- Protection: Over Voltage/Short Circuit/Over Current/Over Temperature
- Packaged Unit Weight: 1.54 lbs
- Carton Quantity: 12 pcs

Inner Box Dimensions:



REV	DESCRIPTION	DATE	BY
A			
B			

ITEM NUMBER	S-12V0-12A5-IDG30	PART TITLE	Energy Efficient 12 VDC / 12.5A Universal Input Power Supply
PART NUMBER	SA-1212A5IV	 CONDOR ELECTRONICS, INC. T: 408-745-7141 F: 408-745-0439 780 Montague Expy. Ste. 406 San Jose, CA 95131 USA sales@condorelectronics.net	
DATE	11.04.2013		
APPROVAL	CB		
UNIT	mm		
REV	Ø		