





White Inner Box Dimensions



General Specifications

- Input: 100~240Vac/ 47~63Hz
- Output: +18VDC/0~3600mA Regulated
- DC Cord: 4.9FT, 18AWG
- Operating/Storage Temperature: 0°C~+40°C~ -20°C~+80°C
- Operating/Storage Humidity: 20%~80%RH/10%~90%RH
- M.T.B.F.: 300,000 Hrs. Minimum (25°C By MIL -HDBK-217F)
- Approvals: UL/ CUL/ FCC/ LPS/ PSE/ CCC/ CHINA ROHS/ RCM/ TUV/ CE/ WEEE/ ROHS/ V
- Meets Energy Efficiency Level V Standards
- Protection: Over Voltage/Short Circuit/Over Current
- Packaged Unit Weight: .70 lbs

REV	DESCRIPTION	DATE	BY
A			
B			

ITEM NUMBER	S-18V0-3A6-IDG30	PART TITLE	Energy Efficient 18VDC/ 3.6A Universal Input Power Supply
PART NUMBER	SA-183A6IV	 CONDOR ELECTRONICS, INC. T: 408-745-7141 F: 408-745-0439 780 Montague Expy. Ste. 406 San Jose, CA 95131 USA sales@condorelectronics.net	
DATE	12.11.2013		
APPROVAL	CB		
UNIT	MM		
REV	Ø		