

Output Plug and Polarity are Dependent on Customer Requirements

Inner Box Dimensions:

General Specifications

Input: 100~240Vac/ 47~63Hz

Output: +19VDC/0~8400mA Regulated

DC Cord: 4.9 FT, 16 AWG

Operating/Storage Temperature: 0°C ~+40°C/ -20°C~+80°C

Operating/Storage Humidity: 20%~80%RH/ 10%~90%RH

■ Approvals: UL/ CUL/ FCC/ PSE/ BSMI / TUV/ CE/ WEEE/ ROHS/ V

Meets Energy Efficiency Level V Standards

Protection: Over Voltage/Short Circuit/Over Current/Over Temperature

Packaged Unit Weight: 1.54 lbs

Carton Quantity: 20 pcs

Build to Order

REV	DESCRIPTION	DATE	BY
Α			
В			

ITEM NUMBER	S-19V0-8A4-IDG30	
PART NUMBER	SA-198A4IV	
DATE	03.10.2014	
APPROVAL	СВ	
UNIT	mm	
REV	Ø	

		7
	\searrow	48.2
198.6	10	**
	YX	

PART

TITLE

Energy Efficient 19 VDC / 8.4A Universal Input Power Supply

T: 408-745-7141 F: 408-745-0439 780 Montague Expy. Ste. 406 San Jose, CA 95131 USA sales@condorelectronics.net