





Output Plug and Polarity are Dependent on Customer Requirements

General Specifications

- Input: 100~240Vac/ 47~63Hz
- Output: +20VDC/0~6000mA Regulated
- DC Cord: 6FT, 16AWG, With Ferrite
- Operating/Storage Temperature: 0°C ~+40°C/ -20°C~+60°C
- Operating/Storage Humidity: 20%~80%RH/10%~90%RH
- M.T.B.F.: 50,000 Hrs. Minimum (25°C Ambient Temp., Full Load)
- Approvals: UL/ CUL/ FCC/ PSE/ BSMI / CCC/ RCM/ TUV/ CE/ WEEE/ ROHS/ V
- Meets Energy Efficiency Level V Standards
- Protection: Over Voltage/Short Circuit/Over Current/Over Temperature
- Packaged Unit Weight: 1.45 lbs
- Box Quantity: 24 pcs

White Inner Box Dimensions



REV	DESCRIPTION	DATE	BY
A			
B			

ITEM NUMBER	S-20V0-6A0-IDG30	PART TITLE	Energy Efficient 20VDC/ 6A Universal Input Power Supply
PART NUMBER	SA-206A01V	 CONDOR ELECTRONICS, INC. T: 408-745-7141 F: 408-745-0439 780 Montague Expy. Ste. 406 San Jose, CA 95131 USA sales@condorelectronics.net	
DATE	10.17.2013		
APPROVAL	CB		
UNIT	mm		
REV	Ø		