



Output Plug
and Polarity are
Dependent on
Customer
Requirements


General Specifications

- Input: 100~240Vac/ 47~63Hz
- Output: +6VDC/0~1000mA Regulated
- DC Cord: 6 FT, 22AWG
- Operating/Storage Temperature: 0°C ~+40°C/ -20°C~+70°C
- Operating/Storage Humidity: 10%~95%RH/ 10%~95%RH
- Approvals: UL/ CUL/ FCC/ LPS/ PSE/ BS/ RCM/ TUV/ CE/ WEEE/ ROHS/ V
- Meets Energy Efficiency Level V Standards
- Protection: Over Voltage/Short Circuit
- Packaged Unit Weight: 0.38 lbs (Complete Set); 0.20lbs (US Only)
- Carton Quantity: 60 pcs
- Can Be Used As Desktop Supply When All Interchangeables are Removed (See IEC-320-C8 Inlet)
- Interchangeable Input Plugs Sold As A Set or Individually (Country Specific)

Inner Box Dimensions:



For U.S. Only



For Complete International Set

REV	DESCRIPTION	DATE	BY
A			
B			

ITEM NUMBER	S-6V0-1A0-U30	PART TITLE	Interchangeable Wall Plug-In 6VDC/1.0A Power Supply – Level V
PART NUMBER	SA-061A0P	 CONDOR ELECTRONICS, INC. T: 408-745-7141 F: 408-745-0439 780 Montague Expy. Ste. 406 San Jose, CA 95131 USA sales@condorelectronics.net	
DATE	12.02.13		
APPROVAL	CB		
UNIT	mm		
REV	Ø		