





**Output Plug
and Polarity are
Dependent on
Customer
Requirements**

General Specifications

- Input: 100~240Vac/ 47~63Hz
- Output: +9VDC/0~17000mA Regulated
- DC Cord: 6 FT, 20 AWG
- Operating/Storage Temperature: 0°C ~+40°C/ -10°C~+70°C
- Operating/Storage Humidity: 20%~80%RH/ 10%~95%RH
- Approvals: UL/ CUL/ FCC/ LPS/ PSE/ BSMI/ CCC/ I RAM/ RCM/ TUV/ CE/ WEEE/ ROHS/ V
- Meets Energy Efficiency Level V Standards
- Protection: Over Voltage/Short Circuit
- Packaged Unit Weight: .53 lbs
- Carton Quantity: 60 pcs
- Interchangeable Input Plugs Sold As A Set or Individually (Country Specific)
- Build to Order

Inner Box Dimensions



REV	DESCRIPTION	DATE	BY
A			
B			

ITEM NUMBER	S-9V0-1A7-U30	PART TITLE	Energy Efficient 9VDC/1.2A Universal Input Power Supply
PART NUMBER	SA-091A7P	 CONDOR ELECTRONICS, INC. T: 408-745-7141 F: 408-745-0439 780 Montague Expy. Ste. 406 San Jose, CA 95131 USA sales@condorelectronics.net	
DATE	01.03.2014		
APPROVAL	CB		
UNIT	mm		
REV	Ø		