

Output Plug and Polarity are Dependent on Customer Requirements

Inner Box Dimensions:

General Specifications

Input: 100~240Vac/ 47~63Hz

Output: +18VDC/0~1000mA Regulated

DC Cord: 5 FT, 20AWG

Operating/Storage Temperature: 0°C ~+40°C/ -10°C~+70°C

Operating/Storage Humidity: 20%~80%RH/ 10%~90%RH

■ Approvals: UL/CUL/FCC/LPS/PSE/BSMI/RCM/TUV/CE/WEEE/ROHS/V

Meets Energy Efficiency Level V Standards

Protection: Over Voltage/Short Circuit

Packaged Unit Weight: .35 Lbs

Carton Quantity: 60 Pcs

Interchangeable Input Plugs Available As A Set
Or Sold Individually (Country Specific).

REV	DESCRIPTION	DATE	BY
Α			
В			

ITEM NUMBEI	۲	S-18V0-1A0-U30
PART NUMBE	R	SA-181A0P
DAT	E	11.15.2013
APPROV.	4 <i>L</i>	СВ
UNI	τŢ	mm
RE	/Τ	Ø

	_
6	5
50 75	

Energy Efficient 18VDC/ 1A Universal Input Power Supply



PART

TITLE

CONDOR ELECTRONICS, INC. T: 408-745-7141 F: 408-745-0439 780 Montague Expy. Ste. 406 San Jose, CA 95131 USA sales@condorelectronics.net