


Output Plug
and Polarity are
Dependent on
Customer
Requirements


General Specifications

- Input: 100~240Vac/ 47~63Hz
- Output: +19VDC/0~2100mA Regulated
- DC Cord: 5 FT, 20 AWG
- Operating/Storage Temperature: 0°C ~+40°C/ -10°C~+70°C
- Operating/Storage Humidity: 20%~80%RH/ 10%~90%RH
- Approvals: UL/ CUL/ FCC/ LPS/ PSE/ RCM/ TUV/ CE/ WEEE/ ROHS/ V
- Meets Energy Efficiency Level V Standards
- Protection: Over Voltage/Short Circuit
- Packaged Unit Weight: .53 Lbs
- Carton Quantity: 60 pcs
- Interchangeable Input Plugs Sold As A Set
Or individually (Country Specific).

Inner Box Dimensions:



REV	DESCRIPTION	DATE	BY
A			
B			

ITEM NUMBER	S-19V0-2A1-U30	PART TITLE	Energy Efficient 19VDC/2.1A Power Supply
PART NUMBER	SA-192A1P	 CONDOR ELECTRONICS, INC. T: 408-745-7141 F: 408-745-0439 780 Montague Expy. Ste. 406 San Jose, CA 95131 USA sales@condorelectronics.net	
DATE	11.15.2013		
APPROVAL	CB		
UNIT	mm		
REV	Ø		