



# H03N60 Series

N-Channel Power Field Effect Transistor

## Description


This high voltage MOSFET uses an advanced termination scheme to provide enhanced voltage-blocking capability without degrading performance over time. In addition, this advanced MOSFET is designed to withstand high energy in avalanche and commutation modes. The new energy efficient design also offers a drain-to-source diode with a fast recovery time. Designed for high voltage, high speed switching applications in power supplies, converters and PWM motor controls, these devices are particularly well suited for bridge circuits where diode speed and commutating safe operating areas are critical and offer additional and safety margin against unexpected voltage transients.

## Features

- Robust High Voltage Termination
- Avalanche Energy Specified
- Source-to-Drain Diode Recovery Time Comparable to a Discrete Fast Recovery Diode
- Diode is Characterized for Use in Bridge Circuits
- $I_{DSS}$  and  $V_{DS(on)}$  Specified at Elevated Temperature

## Absolute Maximum Ratings

| Symbol         | Parameter   | Value      | Units                     |
|----------------|---|------------|---------------------------|
| $I_D$          | Drain to Current (Continuous)   | 3          | A                         |
| $I_{DM}$       | Drain to Current (Pulsed)   | 12         | A                         |
| $V_{GS}$       | Gate-to-Source Voltage (Continue)   | $\pm 30$   | V                         |
| $P_D$          | Total Power Dissipation ( $T_C=25^\circ\text{C}$ )  |            |                           |
|                | H03N60E (TO-220AB)  | 55         | W                         |
|                | H03N60F (TO-220FP)  | 28         |                           |
|                | Derate above $25^\circ\text{C}$   |            |                           |
|                | H03N60E (TO-220AB)  | 0.4        | $\text{W}/^\circ\text{C}$ |
|                | H03N60F (TO-220FP)  | 0.33       |                           |
| $T_j, T_{stg}$ | Operating and Storage Temperature Range   | -55 to 150 | $^\circ\text{C}$          |
| $E_{AS}$       | Single Pulse Drain-to-Source Avalanche Enrgy- $T_j=25^\circ\text{C}$<br>( $V_{DD}=100\text{V}$ , $V_{GS}=10\text{V}$ , $I_L=2\text{A}$ , $L=10\text{mH}$ , $R_G=25\Omega$ ) | 35         | mJ                        |
| $T_L$          | Maximum Lead Temperature for Soldering Purposes, 1/8"<br>from case for 10 seconds   | 260        | $^\circ\text{C}$          |





### Thermal Characteristics

| Symbol          | Parameter                                   | Value    |     | Units |
|-----------------|---|----------|-----|-------|
| $R_{\theta JC}$ | Thermal Resistance Junction to Case Max.    | TO-220AB | 2   | °C/W  |
|                 |   | TO-220FP | 3.3 |       |
| $R_{\theta JA}$ | Thermal Resistance Junction to Ambient Max. | 62.5     |     | °C/W  |

### Electrical Characteristics (T<sub>j</sub>=25°C, unless otherwise specified)

| Symbol        | Characteristic   | Min. | Typ. | Max. | Unit     |
|---------------|--|------|------|------|----------|
| $V_{(BR)DSS}$ | Drain-Source Breakdown Voltage ( $V_{GS}=0V, I_D=250\mu A$ )                                   | 600  | -    | -    | V        |
| $I_{DSS}$     | Drain-Source Leakage Current ( $V_{DS}=600V, V_{GS}=0V$ )                                      | -    | -    | 1    | $\mu A$  |
|               | Drain-Source Leakage Current ( $V_{DS}=480V, V_{GS}=0V, T_J=125^\circ C$ )                     | -    | -    | 50   | $\mu A$  |
| $I_{GSSF}$    | Gate-Source Leakage Current-Forward ( $V_{gsf}=30V, V_{DS}=0V$ )                               | -    | -    | 100  | nA       |
| $I_{GSSR}$    | Gate-Source Leakage Current-Reverse ( $V_{gsr}=-30V, V_{DS}=0V$ )                              | -    | -    | -100 | nA       |
| $V_{GS(th)}$  | Gate Threshold Voltage ( $V_{DS}=V_{GS}, I_D=250\mu A$ )                                       | 2    | -    | 4    | V        |
| $R_{DS(on)}$  | Static Drain-Source On-Resistance ( $V_{GS}=10V, I_D=1.5A$ )*                                  | -    | -    | 4    | $\Omega$ |
| $g_{FS}$      | Forward Transconductance ( $V_{DS}\geq 50V, I_D=1.5A$ )*                                       | 1    | -    | -    | mhos     |
| $C_{iss}$     | Input Capacitance  | -    | 465  | -    | pF       |
| $C_{oss}$     | Output Capacitance   | -    | 66   | -    |          |
| $C_{rss}$     | Reverse Transfer Capacitance   | -    | 13   | -    |          |
| $t_{d(on)}$   | Turn-on Delay Time   | -    | 12   | -    | ns       |
| $t_r$         | Rise Time  | -    | 21   | -    |          |
| $t_{d(off)}$  | Turn-off Delay Time  | -    | 30   | -    |          |
| $t_f$         | Fall Time  | -    | 24   | -    |          |
| $Q_g$         | Total Gate Charge  | -    | 18   | 30   | nC       |
| $Q_{gs}$      | Gate-Source Charge   | -    | 5    | -    |          |
| $Q_{gd}$      | Gate-Drain Charge  | -    | 12   | -    |          |
| $L_D$         | Internal Drain Inductance (Measured from the drain lead 0.25" from package to center of die)   | -    | 4.5  | -    | nH       |
| $L_S$         | Internal Drain Inductance (Measured from the drain lead 0.25" from package to source bond pad) | -    | 7.5  | -    | nH       |

\*: Pulse Test: Pulse Width  $\leq 300\mu s$ , Duty Cycle  $\leq 2\%$







### Source-Drain Diode

| Symbol   | Characteristic        |  | Min. | Typ. | Max. | Units |
|----------|-----------------------|--|------|------|------|-------|
| $V_{SD}$ | Forward On Voltage(1) | $I_S=3A, V_{GS}=0V, T_J=25^\circ C$        | -    | -    | 1.6  | V     |
| $t_{on}$ | Forward Turn-On Time  | $I_S=3A, V_{GS}=0V, d_{is}/d_t=100A/\mu s$ | -    | **   | -    | ns    |
| $t_{rr}$ | Reverse Recovery Time |  | -    | 340  | -    | ns    |

\*\* : Negligible, Dominated by circuit inductance



### Characteristics Curve





### TO-220AB Dimension

3-Lead TO-220AB  
Plastic Package  
HSMC Package Code: E

**Marking:**

Pb Free Mark  
Pb-Free: "●" (Note)  
Normal: None

Date Code      Control Code

Note: Green label is used for pb-free packing

Pin Style: 1.Gate 2 & Tab.Drain 3.Source

**Material:**

- Lead solder plating: Sn60/Pb40 (Normal), Sn/3.0Ag/0.5Cu or Pure-Tin (Pb-free)
- Mold Compound: Epoxy resin family, flammability solid burning class: UL94V-0

| DIM | Min.  | Max.   |
|-----|-------|--------|
| A   | 5.58  | 7.49   |
| B   | 8.38  | 8.90   |
| C   | 4.40  | 4.70   |
| D   | 1.15  | 1.39   |
| E   | 0.35  | 0.60   |
| F   | 2.03  | 2.92   |
| G   | 9.66  | 10.28  |
| H   | -     | *16.25 |
| I   | -     | *3.83  |
| J   | 3.00  | 4.00   |
| K   | 0.75  | 0.95   |
| L   | 2.54  | 3.42   |
| M   | 1.14  | 1.40   |
| N   | -     | *2.54  |
| O   | 12.70 | 14.27  |
| P   | 14.48 | 15.87  |

\*: Typical, Unit: mm

### TO-220FP Dimension

3-Lead TO-220FP  
Plastic Package  
HSMC Package Code: F

**Marking:**

Pb Free Mark  
Pb-Free: "●" (Note)  
Normal: None

Date Code      Control Code

Note: Green label is used for pb-free packing

Pin Style: 1.Gate 2.Drain 3.Source

**Material:**

- Lead solder plating: Sn60/Pb40 (Normal), Sn/3.0Ag/0.5Cu or Pure-Tin (Pb-free)
- Mold Compound: Epoxy resin family, flammability solid burning class: UL94V-0

| DIM      | Min.  | Max.  |
|----------|-------|-------|
| A        | 6.48  | 7.40  |
| C        | 4.40  | 4.90  |
| D        | 2.34  | 3.00  |
| E        | 0.45  | 0.80  |
| F        | 9.80  | 10.36 |
| G        | 3.10  | 3.60  |
| I        | 2.70  | 3.43  |
| J        | 0.60  | 1.00  |
| K        | 2.34  | 2.74  |
| L        | 12.48 | 13.60 |
| M        | 15.67 | 16.20 |
| N        | 0.90  | 1.47  |
| O        | 2.00  | 2.96  |
| α1/2/4/5 | -     | *5°   |
| α3       | -     | *27°  |

\*: Typical, Unit: mm

#### Important Notice:

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of HSMC.
- HSMC reserves the right to make changes to its products without notice.
- **HSMC semiconductor products are not warranted to be suitable for use in Life-Support Applications, or systems.**
- HSMC assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.

#### Head Office And Factory:


- **Head Office** (Hi-Sincerity Microelectronics Corp.): 10F., No. 61, Sec. 2, Chung-Shan N. Rd. Taipei Taiwan R.O.C.  
Tel: 886-2-2521-2056 Fax: 886-2-2563-2712
- **Factory 1:** No. 38, Kuang Fu S. Rd., Fu-Kou Hsin-Chu Industrial Park Hsin-Chu Taiwan. R.O.C  
Tel: 886-3-598-3621~5 Fax: 886-3-598-2931



### Soldering Methods for HSMC's Products

1. Storage environment: Temperature=10°C~35°C Humidity=65%±15%
2. Reflow soldering of surface-mount devices

Figure 1: Temperature profile



| Profile Feature                                      | Sn-Pb Eutectic Assembly | Pb-Free Assembly |
|--|-------------------------|------------------|
| Average ramp-up rate ( $T_L$ to $T_P$ )              | <3°C/sec                | <3°C/sec         |
| Preheat  |                         |                  |
| - Temperature Min ( $T_{smin}$ )                     | 100°C                   | 150°C            |
| - Temperature Max ( $T_{smax}$ )                     | 150°C                   | 200°C            |
| - Time (min to max) ( $t_s$ )                        | 60~120 sec              | 60~180 sec       |
| $T_{smax}$ to $T_L$                                  |                         |                  |
| - Ramp-up Rate                                       | <3°C/sec                | <3°C/sec         |
| Time maintained above:                               |                         |                  |
| - Temperature ( $T_L$ )                              | 183°C                   | 217°C            |
| - Time ( $t_L$ )                                     | 60~150 sec              | 60~150 sec       |
| Peak Temperature ( $T_P$ )                           | 240°C +0/-5°C           | 260°C +0/-5°C    |
| Time within 5°C of actual Peak Temperature ( $t_P$ ) | 10~30 sec               | 20~40 sec        |
| Ramp-down Rate                                       | <6°C/sec                | <6°C/sec         |
| Time 25°C to Peak Temperature                        | <6 minutes              | <8 minutes       |

### 3. Flow (wave) soldering (solder dipping)

| Products         | Peak temperature | Dipping time |
|------------------|------------------|--------------|
| Pb devices.      | 245°C ±5°C       | 10sec ±1sec  |
| Pb-Free devices. | 260°C ±5°C       | 10sec ±1sec  |