


Dual series switching diode

Lead free product

Halogen-free type

DAN217UGH



FEATURES

- Fast switching speed.
- Small surface mounting type.
- Two diode elements are connected in series.
- Non-Halogen.
- Surface mount package ideally suited for automatic insertion

APPLICATIONS

- For general purpose switching application.

MAXIMUM RATING @ Ta=25℃ unless otherwise specified

Parameter	Symbol	Value	Unit
Non repetitive peak reverse voltage	V_{RM}	80	V
Repetitive peak reverse voltage Working peak reverse voltage DC Reverse voltage	V_{RRM} V_{RWM} V_R	80	V
Peak forward surge current @t=10ms	I_{FSM}	1	A
Forward continuous current	I_{FM}	300	mA
Average rectified output current	I_O	100	mA
Power dissipation	P_d	200	mW
Operating and storage temperature range	T_j, T_{STG}	-55-125	℃

ELECTRICAL CHARACTERISTICS @ $T_a=25^\circ\text{C}$ unless otherwise specified

Parameter	Symbol	Test conditions	MIN	MAX	UNIT
Reverse breakdown voltage	$V_{(BR)}$	$I_R=100\mu\text{A}$	80		V
Reverse voltage leakage current	I_R	$V_R=70\text{V}$		0.1	μA
Forward voltage	V_F	$I_F=100\text{mA}$		1200	mV

TYPICAL CHARACTERISTICS @ $T_a=25^\circ\text{C}$ unless otherwise specified

