

# RLM G5i Performer

With its compact design and sealed optics, the RLM G5i Performer is an ideal all-round projector suitable to both the rental as well as staging markets.



Feature-rich and ready to use, the RLM G5i Performer allows everything from seamless switching to picture-in-picture and enables you to show up to 4 sources simultaneously on-screen.

With its sealed optics (prism and DMD's), a dedicated lens range and compatibility with the existing SLM Projector lenses, the RLM G5i Performer becomes the ideal staging or corporate rental projector.

**BARCO**

Visibly yours

**Product specifications****RLM G5i Performer**

<b>Light output</b>	4500 ANSI Lumen
<b>Resolution</b>	1024 x 768 (native)
<b>Contrast ratio</b>	1000 : 1 (full field)
<b>High contrast mode</b>	Available with special lenses
<b>Brightness uniformity</b>	> 90%
<b>Lamp</b>	2 x 250 W mercury max. lifetime: 1500 hrs typ. lifetime: 1000 hrs min. lifetime: 750 hrs
<b>Noise level (@ 20°C - 68°F)</b>	42 dBa
<b>Noise level (@ 40°C - 104°F)</b>	46,5 dBa
<b>Ambient temperature</b>	Max 40°C (104°F)
<b>Power consumption</b>	700 W
<b>Mains Voltage</b>	92-240 V
<b>Weight</b>	Projector: 25 kg (56 lbs) Frame: 5 kg (11 lbs)
<b>Dimensions (WxLxH)</b>	705 x 707,8 x 316,5 mm
<b>Light shutter</b>	Standard
<b>Sealed DLP™ core</b>	Standard
<b>ScenergiX</b>	Standard horizontal and vertical electronic edge blending
<b>Seamless Switching</b>	Standard (wipes, fades, ...)
<b>Picture-in-picture</b>	Up to 4 sources simultaneously (2 data, 1 video and 1 SDI)
<b>Digital zoom</b>	Standard
<b>Lens encoders</b>	On zoom and focus (with TLD lenses)
<b>Linked Constant Light Output</b>	not available
<b>Input source compatibility</b>	1600 x 1200 (max. input)
<b>Fixed Inputs</b>	<ul style="list-style-type: none"><li>■ 1x configurable 5&amp;nbsp;cable (BNC)</li><li>■ 1x composite Video (BNC)</li><li>■ 1x S-Video (4-pin DIN)</li><li>■ 1x&amp;nbsp;analogue RGB&amp;nbsp;(D15&amp;nbsp;Connector)</li><li>■ 1x SDI ( + loop through)</li><li>■ 1x DVI (Digital Visual Interface)</li></ul>
<b>Modular inputs</b>	not available
<b>Control</b>	<ul style="list-style-type: none"><li>■ 1 x RS-232 / 422 IN</li><li>■ 1&amp;nbsp;x XLR female (2 way)</li><li>■ build-in RF remote transceiver (optional)</li></ul>
<b>Order Information</b>	Projector Body: R9010320 Spare Dual Lamp:R9852940