

iQ Praxis G300



Barco's **iQ Praxis G300** projector can be fully tailored to meet your requirements and budget. Based on your presentation needs, you can choose out of a **set of individual options** (like advanced picture-in-picture, seamless source switching, logo storage etc) or application specific **Value Packs**. This versatile LCD projector with **XGA resolution** delivers an amazing brightness level of **3,500 ANSI lumens**. The iQ Series is the smartest choice for compelling presentations in any venue, from brightly lit boardrooms to larger conference centers.

BARCO

Visibly yours

Product specifications**iQ Praxis G300**

Light output	3,500 ANSI lumen
Brightness uniformity	Brightness uniformity: >95 % for the total screen
LCD panels	3 active matrix 1.3" diagonal XGA polysilicon LCD panels with Micro Lens Arrays and a resolution of 1024 x 768 pixels (aspect ratio 4:3). LCD panels are selected for a minimum of pixel defects.
Resolution	1024 x 768 (native)
Lamp	2x 200 Watt UHP lamp, in lamp housing, pre-aligned for max. light output. Typical lifetime: 1500 h/lamp. 1500 hours in Dual Lamp Mode or max. 3000 hours/set in Single Lamp Mode.
Lenses	Fixed focal length lenses are available with a throw ratio of 0.85:1 (very short throw ratio, specially designed for rear screen on-axis projection) or 7.0:1 (long throw). Variable focus lenses with a throw distance of 1.3-1.8,1.9-2.6,3.0-6.0 times the screen width
Screen size	From 1-6 m/3-20 ft.
Contrast	>400 : 1 (full white/full black)
Scan Frequencies	Horizontal 15 kHz - 110 kHz Vertical 25 Hz - 150 Hz
Compatibility	The iQ Praxis G300 is compatible with: <ul style="list-style-type: none">• All current video sources (PAL,SECAM, NTSC) in Composite, S-VHS, Component or RGB formats• All currently proposed HDTV, extended and improved television standards (1080i, 720p)• All computer graphics formats from VGA, SVGA, XGA, SXGA to UXGA• Most Macintosh computers• Electronic workstations with a resolution up to 1600 x 1200 pixels at 75 Hz• Most computer sources with a pixel clock up to 160 MHz• DVI sources up to SXGA
Inputs	1x Configurable 5-Wire (BNC) for: Composite Video, S-Video, Component Video , RGBHV, RGBS, RGsB. 1x Composite Video (BNC) 1x S-Video (4-pin mini-DIN) (up to 3 S-Video's when combining BNC's) 1x VGA (D15 connector) 1x DVI (Digital Visual Interface)
Dimensions (WxLxH)	Projector body with cable basket: 415 mm (Max W) x 195 mm (Max H) x 565 mm (Max D) Projector body without cable basket: 415 mm (Max W) x 195 mm (Max H) x 487 mm (Max D)
Communication	1x D9 connectors for RS232 In/Out 1x spherical IR receiver
Noise Level	<37dB
AC power	Power factor pre-regulated SMPS, 90-254 VAC / 50-60Hz
Power consumption	Max 520 Watt
Power Dissipation	Max 1775 BTU/h
Weight	Net weight: Body only 12.9 kg / 28.5 lbs. Shipping weight: <ul style="list-style-type: none">• without lens max.17.5 kg / 38.5 lbs.• with lens: max.20 kg / 44 lbs.
Lens Shift	QVD Lenses Motorized V shift: -30% +120%