


MDRC-1119

19-inch pathology display



The MDRC-1119 is a 1 MegaPixel pathology display and brings reliable, DICOM-compliant images to a broad palette of imaging applications.

Consistent DICOM images, anywhere, anytime

The MDRC-1119's **high-quality LCD panel** presents pathology images with better contrast, higher brightness and a wider viewing angle than conventional computer monitors.

Advanced **Backlight Output Stabilization (BLOS) technology** ensures fast power-up and continuous LCD backlight stability, resulting in long-term image consistency.

And thanks to the integrated DICOM Part 14 Look-Up Table, the MDRC-1119 is **DICOM-compliant "out-of-the-box"**.

BARCO

Visibly yours

Product specifications**MDRC-1119**

Screen technology	TFT Color LCD
Active screen size (diagonal)	483 mm (19.0")
Active screen size (H x V)	301 x 376 mm (11.9 x 14.8")
Aspect ratio (H:V)	5:4
Resolution	1MP (1280 x 1024)
Pixel pitch	0.2940 mm
Color imaging	Yes
Gray imaging	No
Color support	16.8 million
Viewing angle (H, V)	178°
Uniform Luminance Technology (ULT)	No
Per Pixel Uniformity (PPU)	No
Ambient Light Compensation (ALC)	No
Backlight Output Stabilization (BLOS)	Yes
I-Guard	No
Maximum luminance	300 cd/m ²
DICOM calibrated luminance	180 cd/m ²
Contrast ratio	1300:1
Response time (Tr + Tf)	10 ms
Scanning frequency (H; V)	31.5-79.95 kHz; 50-75 Hz
Housing color	Dark gray
Video input signals	DVI-D Single Link VGA (DB15)
Video inout terminals	Separate H&V sync Composite sync on H Sync on Green supported
USB ports	1 upstream, 2 downstream
USB standard	1.1
Power requirements (nominal)	100-240V
Power consumption (nominal)	35W
Power save mode	Yes
Power management	DVI-DMPM states supported Power On state Active-Off state DPMS states supported
Dot clock	165 MHz
OSD languages	English, French, German, Spanish, Italian, Dutch, Simplified Chinese, Traditional Chinese, Japanese, Korean
Dimensions with stand (W x H x D)	Landscape: 418 x 535~425 x 223 mm
Dimensions w/o stand (W x H x D)	Portrait: 346 x 418 x 70 mm Landscape: 418 x 346 x 70 mm
Dimensions packaged (W x H x D)	502 x 494 x 294 mm
Net weight with stand	8.4 kg
Net weight w/o stand	5.7 kg
Net weight packaged with stand	11.4 kg
Net weight packaged w/o stand	8.7 kg
Height adjustment range	120 mm
Tilt	-0° / +10°
Swivel	-45° / +45°

Product specifications	MDRC-1119
Pivot	90°
Mounting standard	VESA (100 mm)
Screen protection	Optional protective front cover
Recommended modalities	CT, MR, US, DR, CR, NM, Film
Certifications	EN 60601-1-2 (2001), EN 55011 (Class B), IEC 61000-3-2, IEC 61000-3-3, IEC 61000-4-2, IEC 61000-4-3, IEC 61000-4-4, IEC 61000-4-5, IEC 61000-4-11, IEC 61000-4-6, IEC 61000-4-8, CE, EN 60601-1 Medical Part 1, FCC B, c-ul, PSE, BSMII, VCCI, CCC, KCC, CSA c22.2No601.1, UL50501-1
Supplied accessories	User manual Video cables (DVI Single Link, Analog) Main cables (UK, European (CEBEC/KEMA), USA (UL/CSA; adaptor plug NEMA 5-15P), Chinese (CCC)) External power supply
Optional accessories	Barco External Medical LCD Display Sensor Barco MDRC-1119 Clinical Review Medical LCD Display Protective Front Cover Kit
QA software	MediCal QAWeb
Units per pallet	24
Pallet dimensions (W x H)	800 x 1200 mm
Warranty	3 years