

SG320200A (320 DOTS X 200 DOTS)

FEATURES

- . NO BUILT-IN CONTROLLER
- . 4.5V POWER SUPPLY
- . +3.3V POWER SUPPLY
- . 1/200 DUTY CYCLE
- . 4-BIT PARALLEL INTERFACE

MECHANICAL DATA

ITEM	DIMENSIONS	UNIT
Module Size (W x H x T)	110.4 x 57.0 x 7.4	mm
Viewing Area (W x H)	82.0 x 46.0	mm
Active Area (W x H)	80.0 x 44.0	mm
Dot Size (W x H)	0.22 x 0.195	mm
Dot Pitch (W x H)	0.25 x 0.22	mm

INTERFACE PIN CONNECTIONS

NO.	SYMBOL	LEVEL	FUNCTION
1	EL1	-	EL Backlight
2	EL2	-	EL Backlight
3	NC	-	No Connection .
4	VDD	3.3V	Power Supply Voltage
5	FLM	H	Frame Start Signal
6	M	H/L	Control Signal For AC Driving
7	CL1	H→L	Common Driver Data Shift Signal
8	/DISPOFF	H/L	Display OFF.Active LOW
9	VSS	0V	Power Supply Ground
10	CL2	H→L	Clock Pulse For Segment Shift Register
11~14	DB3~DB0	H/L	Data Bus Line
15	VDD	3.3V	Power Supply Voltage
16	VSS	0V	Power Supply Ground

ABSOLUTE MAXIMUM RATINGS

ITEM	SYMBOL	MIN.	TYP.	MAX.	UNIT
Supply Voltage For Logic	VDD-VSS	0	-	7	V
Supply Voltage For LCD Drive	VDD-Vo	0	-	30	V
Input Voltage	VI	VSS	-	VDD	V

ELECTRICAL CHARACTERISTICS

ITEM	SYMBOL	CONDITION	MIN.	TYP.	MAX.	UNIT	
Supply Voltage For Logic	VDD-VSS	-	2.7	3.3	4.5	V	
LCD Supply Voltage	VDD-Vo	VDD=3.3V Ta=25.	19.8	22.1	23.4	V	
Supply Current	IDD	VDD=3.3V	-	4.5	6.5	mA	
Input Voltage	"HIGH" Level	V _{IH}	-	2.2	-	VDD	V
	"LOW" Level	V _{IL}	-	-	-	0.6	V
Output Voltage	"HIGH" Level	V _{OH}	-	2.4	-	-	V
	"LOW" Level	V _{OL}	-	-	-	0.4	V

EXTERNAL DIMENSIONS

