

PAX-6™

6-Watt Precision-Aligned Pulsed Xenon Light Source



Overview

The PAX-6™ by Excelitas is a 6 Watt Precision-Aligned Pulsed Xenon Light Source which is 50% more compact than existing flash lamp systems. The compact, integrated solution contains the flash lamp, trigger circuit, and power supply in an EMI-suppressant enclosure.

The PAX-6 was designed specifically in response to OEMs' needs for precision alignment and features a pre-aligned arc position precisely located relative to a datum feature on the mounting surface of the case. Available in two arc orientations, the PAX-6's pre-aligned arc position allows for "plug and play" field replacement, eliminating alignment time and reducing OEMs' costs and machine down time.

The PAX-6 offers a wide range of flash energy levels and 6 Watts average power in a compact, pre-aligned module. It utilizes Excelitas' high stability short arc Xenon flash lamps. Known for their stability and long life characteristics, these Xenon lamps generate light over a continuous spectrum from ultraviolet to infrared.

The PAX family of compact, precision-aligned Xenon light sources are the ideal choice for clinical diagnostic, invitro diagnostics, life sciences, drug discovery, proteomics, and analytical instrumentation applications.

PRODUCT NOTE

PAX Family of Precision-Aligned Xenon Light Sources

Features and Benefits

- Precision alignment—arc position precisely located (+/- 0.05 mm, .002 inches) relative to a datum feature on the mounting surface
- Ease of installation and convenient "plug and play" field replacement
- 50% more compact than existing flash lamp systems
- Long life: $> 2.0 \times 10^9$ flashes
- Spectral range from 120 to 2000+ nm
- Available in two arc orientations
- 6 Watts average power
- Integrated package—flash lamp, trigger circuit and power supply, all in a compact, EMI suppressant enclosure
- Flexible mounting
- Highest flash rate over full power range
- CE marked and RoHS compliant

Applications

- Absorption analysis
- Immunoassay modules
- Fluorimetry
- Spectroradiometry
- Liquid and gas chromatography
- Colorimetry
- UV/VIS/NIR applications

Input Specifications	
Parameter	Specification
Voltage	11-28 VDC
DC Current	1 Amp avg.
Inrush Current	4 Amps peak
Trigger ¹	+5 V, 20-50 mA peak input, 10-100 µs pulse width, leading edge trigger
Vref (Vo/Vref = 127)	3.15 - 4.73 VDC
Internal/External Intensity Adjust	Switch selectable
Input Connector	9-pin D-sub

NOTE 1: Optically Isolated: Internal series resistor = 150 Ω

Part Number Configuration PAX-6AB-C*	
A= Arc Orientation	0 - vertical 1 - horizontal
B = Lamp Type	1 - 1.5 mm arc length, 225 nm cutoff 2 - 1.5 mm arc length, 190 nm cutoff 3 - 1.5 mm arc length, 120 nm cutoff 4 - 3.0 mm arc length, 225 nm cutoff 5 - 3.0 mm arc length, 190 nm cutoff 6 - 3.0 mm arc length, 120 nm cutoff
C = Discharge Capacitor	1 - 0.047 µF 2 - 0.10 µF 3 - 0.22 µF 4 - 0.27 µF

*** Part Number Example:**
PAX-603-1 = vertical arc,
1.5 mm arc length with
120 nm cutoff and 0.047 µF capacitor

Electrical Output	
Parameter	Specification
Main Discharge Voltage	400-600 VDC +/- 2%
Power	6 Watts
Standard Discharge Capacitors	0.047, 0.10, 0.22, 0.27 µF
Flash Rate (Hz)	Fmax = 6/E where E = 1/2CV ²





Light Output	
Parameter	Specification
Spectral Range	120-2000 + nm
Stability ²	< 1% CV
Life time	> 2 x 10 ⁹ Flashes

NOTE 2:
Operating conditions:
0.22 µF discharge
capacitor. 600 VDC
discharge voltage.
10 Hz flash rate.

Environmental	
Parameter	Specification
Operating temperature	0 to 40 °C
Storage temperature	-40 to 90 °C
Humidity	95% RH, non-condensing
Safety Compliance	CE Marked

Operating Conditions					
Part Number	Main Discharge Capacitor (µF)	Main Discharge Voltage (V)	Maximum Input Energy per Flash (mJ)	Maximum Repetition Rate (Hz)	Maximum Average Power (W)
PAX-6AB-1	0.47	400	3.8	1579	6
		500	5.9	1016	
		600	8.5	705	
PAX-6AB-2	0.1	400	8	750	6
		500	12.5	480	
		600	18	333	
PAX-6AB-3	0.22	400	17.5	341	6
		500	27.5	218	
		600	39.6	151	
PAX-6AB-4	0.27	400	21.6	278	6
		500	33.7	178	
		600	48.6	123	

Characteristics




PAX-6 Precision Arc Alignment and Mounting



Arc size	A in [mm]	B in [mm]
1.50 mm	.472 [11.989]	.412 [10.465]
3.00 mm	.501 [12.725]	.383 [9.728]

Notes:


1. Precision mounting requires dowel pins (dia = .1250"/.1252").
2. Mounting kits available as an accessory.
3. Alignment provided from pin center to theoretical intersection of electrode tip as shown.




ARC POSITION 0
"PAX-60B-C"




ARC POSITION 1
"PAX-61B-C"



Mechanical Outline




Mechanical Dimensions



Mechanical Mounting Kits (optional)

- Notes**
 1. Both kits contain fasteners for mounting.
 2. CAD model(s) available for easy integration. (STEP, ACIS or DXF).



Ordering Information

Excelitas has designed an easy to use Evaluation Kit for testing the PAX-6 in your application.

To request additional information, receive a quote, or place an order for the PAX-6, please contact your Customer Support team or visit our website at www.excelitas.com.

All values are nominal; specifications are subject to change without notice.

Excelitas Technologies
 35 Congress Street
 Salem, Massachusetts 01970 USA
 Telephone: (+1) 978.745.3200
 Toll free: (+1) 800.950.3441
 Fax: (+1) 978.745.0894
generalinquiries@excelitas.com
www.excelitas.com

Excelitas Technologies GmbH & Co. KG
 Wenzel-Jaksch-Str. 31
 D-65199 Wiesbaden
 Germany
 Telephone: (+49) 611 492 430
 Fax: (+49) 611 492 165

Asia Headquarters Excelitas Technologies
 47 Ayer Rajah Crescent #06-12
 Singapore 139947
 Telephone: (+65) 6775-2022
 Fax: (+65) 6775-1008

EXCELITAS
 TECHNOLOGIES

For a complete listing of our global offices, visit www.excelitas.com/ContactUs

Copyright ©2011 Excelitas Technologies Corp. All rights reserved. Excelitas® is a registered trademark of Excelitas Technologies Corp. All other trademarks are the property of their respective owners. Excelitas reserves the right to change this document at any time without notice and disclaims liability for editorial, pictorial or typographical errors.