

TECHNICAL DATA
DATA SHEET 4145, REV. -

HERMETIC POWER ULTRAFAST RECTIFIER

DESCRIPTION: A 1200-VOLT, 20 AMP, 50 NSEC ULTRAFAST RECTIFIER IN TO-257 PACKAGE

MAXIMUM RATINGS

All ratings are @ $T_A = 25^\circ\text{C}$ unless otherwise specified


RATING	SYMBOL	MAX.	UNITS
PEAK INVERSE VOLTAGE PER LEG	PIV	1200	Volts
MAX DC OUTPUT CURRENT ($T_C=100^\circ\text{C}$) COMMON CATHODE / ANODE DOUBLER	I_o	20 10	Amps
MAXIMUM SURGE CURRENT ($T_C=25^\circ\text{C}$, $T=8.3$ MSEC) PER LEG	I_{FSM}	80	Amps
REVERSE RECOVERY TIME ($I_f = 1\text{A}$, $dI/dt = 50\text{A}/\mu\text{sec}$, $V_R = 30\text{V}$, $T_C=25^\circ\text{C}$)	t_{rr} (typ) t_{rr} (max)	50 70	nsec nsec
MAXIMUM REVERSE RECOVERY CURRENT ($V_R= 540\text{V}$, $I_F= 12\text{A}$, $dI/dt= 100\text{A} / \text{usec}$)	I_{RM} (typ) I_{RM} (max)	6.5 7.2	Amps
MAXIMUM THERMAL RESISTANCE COMMON CATHODE / ANODE DOUBLER	$R_{\theta JC}$	1.9 3.8	$^\circ\text{C}/\text{W}$
MAXIMUM OPERATING AND STORAGE TEMPERATURE RANGE	Top/Tstg	-55 to + 150	$^\circ\text{C}$

ELECTRICAL CHARACTERISTICS

CHARACTERISTIC	SYMBOL	MAX.	UNITS
MAXIMUM FORWARD VOLTAGE DROP, Pulsed, PER LEG ($I_f = 12$ Amps)	V_f	2.60	Volts
MAXIMUM FORWARD VOLTAGE DROP, Pulsed, PER LEG ($I_f = 12$ Amps)	V_f	2.45	Volts
MAXIMUM REVERSE CURRENT PER LEG $T_C = 25^\circ\text{C}$ $I_r @ 1000\text{V PIV}$	I_r	200	μA
MAXIMUM REVERSE CURRENT PER LEG $T_C = 100^\circ\text{C}$ $I_r @ 1000\text{V PIV}$	I_r	3	mA

TECHNICAL DATA
DATA SHEET 4145, REV. -

MECHANICAL DIMENSIONS: In Inches / mm



TO-257

PINOUT TABLE

DEVICE TYPE	PIN 1	PIN 2	PIN 3
SINGLE RECTIFIER	CATHODE	ANODE	ANODE
DUAL RECTIFIER/COMMON CATHODE (P)	ANODE 1	COMMON CATHODE	ANODE 2
DUAL RECTIFIER/COMMON ANODE (N)	CATHODE 1	COMMON ANODE	CATHODE 2
DUAL RECTIFIER/DOUBLER (D)	ANODE 1	ANODE/ CATHODE	CATHODE 2

TECHNICAL DATA

DISCLAIMER:

- 1- The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact the Sensitron Semiconductor sales department for the latest version of the datasheet(s).
- 2- In cases where extremely high reliability is required (such as use in nuclear power control, aerospace and aviation, traffic equipment, medical equipment, and safety equipment), safety should be ensured by using semiconductor devices that feature assured safety or by means of users' fail-safe precautions or other arrangement.
- 3- In no event shall Sensitron Semiconductor be liable for any damages that may result from an accident or any other cause during operation of the user's units according to the datasheet(s). Sensitron Semiconductor assumes no responsibility for any intellectual property claims or any other problems that may result from applications of information, products or circuits described in the datasheets.
- 4- In no event shall Sensitron Semiconductor be liable for any failure in a semiconductor device or any secondary damage resulting from use at a value exceeding the absolute maximum rating.
- 5- No license is granted by the datasheet(s) under any patents or other rights of any third party or Sensitron Semiconductor.
- 6- The datasheet(s) may not be reproduced or duplicated, in any form, in whole or part, without the expressed written permission of Sensitron Semiconductor.
- 7- The products (technologies) described in the datasheet(s) are not to be provided to any party whose purpose in their application will hinder maintenance of international peace and safety nor are they to be applied to that purpose by their direct purchasers or any third party. When exporting these products (technologies), the necessary procedures are to be taken in accordance with related laws and regulations.