

SENSITRON
SEMICONDUCTOR

TECHNICAL DATA
DATA SHEET 227, REV. B

HERMETIC POWER MOSFET
N-CHANNEL
(Standard and Fast-FET)

DESCRIPTION: A 500 VOLT, 24 AMP, 0.23 $R_{DS(ON)}$ MOSFET IN A HERMETIC TO-254 PACKAGE.
SHD225605: Formerly SHD2253, N-Channel Enhancement Mode.
SHD225606: Formerly SHD2253F, N-Channel Enhancement Mode with Fast Intrinsic Diode.

MAX. RATINGS / ELECTRICAL CHARACTERISTICS (AT $T_j=25^{\circ}C$ UNLESS OTHERWISE SPECIFIED).

PARAMETER	SYMBOL	MIN	TYP	MAX	UNITS
DRAIN TO SOURCE BREAKDOWN VOLTAGE ($V_{GS} = 0\text{ V}$, $I_D = 1.0\text{ mA}$)	BV_{DSS}	500	-	-	Volts
DRAIN TO SOURCE ON STATE RESISTANCE ($V_{GS} = 10\text{ V}$, $I_D = 12.0\text{ A}$)	$R_{DS(ON)}$	-	-	0.23	Ω
CONTINUOUS DRAIN CURRENT ($V_{DS} = 10\text{ V}$, $T_C = 25^{\circ}C$)	I_D	-	-	24	Amps
GATE THRESHOLD VOLTAGE ($V_{DS} = V_{GS}$, $I_D = 250\mu\text{A}$)	$V_{GS(th)}$	2.0	-	4.0	Volts
FORWARD TRANSCONDUCTANCE ($V_{DS}=10\text{V}$, $I_{DS} = 12.0\text{A}$)	g_{fs}	11	21	-	$S(1/\Omega)$
ZERO GATE VOLTAGE DRAIN CURRENT ($V_{DS} = 400\text{V}$) ($V_{GS} = 0\text{V}$, $T_J=125^{\circ}C$)	I_{DSS}	-	-	200 1.0	μA mA
GATE TO SOURCE LEAKAGE ($V_{GS} = \pm 20V_{DC}$, $V_{DS} = 0$)	I_{GSS}	-	-	+/- 100	nA
TOTAL GATE CHARGE ($V_{GS} = 10\text{V}$, $V_{DS} = 250\text{V}$, $I_D = 12.0\text{A}$)	Q_g	-	-	190 160	nC
INPUT CAPACITANCE	C_{iss}	-	4200	-	pF
OUTPUT CAPACITANCE	C_{oss}	-	450	-	
REVERSE TRANSFER CAPACITANCE ($V_{GS} = 0\text{V}$, $V_{DS} = 25\text{V}$, $f = 1.0\text{ Mhz}$)	C_{rss}	-	135	-	


SENSITRON

**TECHNICAL DATA
DATA SHEET 227, REV. B**

SOURCE-DRAIN DIODE RATINGS AND CHARACTERISTICS

PARAMETER	SYMBOL	MIN	TYP	MAX	UNITS
DIODE FORWARD VOLTAGE ($I_S = 24A, V_{GS} = 0V$)	V_{SD}	-	-	1.5	Volts
DIODE REVERSE RECOVERY TIME ($I_F = 24A, di/dt 100 A/\mu s, V_R = 100V$)	t_{rr}	-	600	250	ns

MECHANICAL DIMENSIONS: Inches / mm



TO-254

PINOUT TABLE

DEVICE TYPE	PIN 1	PIN 2	PIN 3
MOSFET TO-254 PACKAGE	DRAIN	SOURCE	GATE

TECHNICAL DATA

DISCLAIMER:

- 1- The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact the Sensitron Semiconductor sales department for the latest version of the datasheet(s).
- 2- In cases where extremely high reliability is required (such as use in nuclear power control, aerospace and aviation, traffic equipment, medical equipment, and safety equipment), safety should be ensured by using semiconductor devices that feature assured safety or by means of users' fail-safe precautions or other arrangement.
- 3- In no event shall Sensitron Semiconductor be liable for any damages that may result from an accident or any other cause during operation of the user's units according to the datasheet(s). Sensitron Semiconductor assumes no responsibility for any intellectual property claims or any other problems that may result from applications of information, products or circuits described in the datasheets.
- 4- In no event shall Sensitron Semiconductor be liable for any failure in a semiconductor device or any secondary damage resulting from use at a value exceeding the absolute maximum rating.
- 5- No license is granted by the datasheet(s) under any patents or other rights of any third party or Sensitron Semiconductor.
- 6- The datasheet(s) may not be reproduced or duplicated, in any form, in whole or part, without the expressed written permission of Sensitron Semiconductor.
- 7- The products (technologies) described in the datasheet(s) are not to be provided to any party whose purpose in their application will hinder maintenance of international peace and safety nor are they to be applied to that purpose by their direct purchasers or any third party. When exporting these products (technologies), the necessary procedures are to be taken in accordance with related laws and regulations.