

SENSITRON

SEMICONDUCTOR

SS4464/US to SS4494/US

TECHNICAL DATA DATA SHEET 5079, Rev -

Zener 1.5W DIODE

- Ultra-low reverse leakage current
- Zener voltage available from 36V to 160V
- Sharp Zener knee
- Metallurgically bonded
- Hermetic, non-cavity glass package


Electrical characteristics – Temperature 25°C unless otherwise noted

Part Number	Nominal Zener Voltage V _Z	Test current I _{ZT}	Max Dynamic Impedance Z _{ZK} @ I _{ZK}	Max Knee Impedance I _{ZK} @ I _{ZK}		Max Continuous Current I _{ZM}	Max Surge Current I _{ZSM}	Maximum Reverse Current I _R @ V _R	
				Ω	mA			μA	V
SS4464/US	9.1	28.0	4	500	0.5	157	1.6	.30	5.46
SS4465/US	10.0	25.0	5	500	.25	143	1.4	.30	8.00
SS4466/US	11.0	23.0	6	550	.25	130	1.3	.30	8.80
SS4467/US	12.0	21.0	7	550	.25	119	1.2	.20	9.60
SS4468/US	13.0	19.0	8	550	.25	110	1.1	.05	10.40
SS4469/US	15.0	17.0	9	600	.25	95	.95	.05	12.00
SS4470/US	16.0	15.5	10	600	.25	90	.90	.05	12.80
SS4471/US	18.0	14.0	11	650	.25	79	.79	.05	14.40
SS4472/US	20.0	12.5	12	650	.25	71	.71	.05	16.00
SS4473/US	22.0	11.5	14	650	.25	65	.65	.05	17.60
SS4474/US	24.0	10.5	16	700	.25	60	.60	.05	19.20
SS4475/US	27.0	9.5	18	700	.25	53	.53	.05	21.60
SS4476/US	30.0	8.5	20	750	.25	48	.48	.05	24.00
SS4477/US	33.0	7.5	25	800	.25	43	.43	.05	26.40
SS4478/US	36.0	7.0	27	850	.25	40	.40	.05	28.80
SS4479/US	39.0	6.5	30	900	.25	37	.37	.05	31.20
SS4480/US	43.0	6.0	40	950	.25	33	.33	.05	34.40
SS4481/US	47.0	5.5	50	1000	.25	30	.30	.05	37.60
SS4482/US	51.0	5.0	60	1100	.25	28	.28	.05	40.80
SS4483/US	56.0	4.5	70	1300	.25	26	.26	.25	44.80
SS4484/US	62.0	4.0	80	1500	.25	23	.23	.25	49.60
SS4485/US	68.0	3.7	100	1700	.25	21	.21	.25	54.40
SS4486/US	75.0	3.3	130	2000	.25	19	.19	.25	60.40
SS4487/US	82.0	3.0	160	2500	.25	17	.17	.25	65.60
SS4488/US	91.0	2.8	200	3000	.25	16	.16	.25	72.80
SS4489/US	100.0	2.5	250	3100	.25	14	.14	.25	80.00
SS4490/US	110.0	2.0	300	4000	.25	13	.13	.25	88.00
SS4491/US	120.0	2.0	400	4500	.25	12	.12	.25	96.00
SS4492/US	130.0	1.9	500	5000	.25	11	.11	.25	104.00
SS4493/US	150.0	1.7	700	6000	.25	9.5	.095	.25	120.00
SS4494/US	160.0	1.6	1000	6500	.25	8.9	.089	.25	128.00

* Dc TA=+150°C IR2


SENSITRON

TECHNICAL DATA
DATA SHEET 5079, Rev -



1N4478 thru 1N4494

PACKAGE STYLE	DIMENSIONS - INCHES (MILLIMETERS)			
	ϕB	ϕD	G	L
Similar to DO-41 (AXIAL)	.028/.032 0.71/0.81	.060/.085 1.52/2.16	.106/.160 2.69/4.06	.80/1.30 20.32/33.02



1N4478U thru 1N4494U

PACKAGE STYLE	DIMENSIONS - INCHES (MILLIMETERS)			
	BL	BD	S	ECT
MELF	.168/.200 4.27/5.08	.091/.103 2.31/2.62	0.003 Min 0.08min	.019/.028 0.48/0.71

DISCLAIMER:

- 1- The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact the Sensitron Semiconductor sales department for the latest version of the datasheet(s).
- 2- In cases where extremely high reliability is required (such as use in nuclear power control, aerospace and aviation, traffic equipment, medical equipment, and safety equipment), safety should be ensured by using semiconductor devices that feature assured safety or by means of users' fail-safe precautions or other arrangement.
- 3- In no event shall Sensitron Semiconductor be liable for any damages that may result from an accident or any other cause during operation of the user's units according to the datasheet(s). Sensitron Semiconductor assumes no responsibility for any intellectual property claims or any other problems that may result from applications of information, products or circuits described in the datasheets.
- 4- In no event shall Sensitron Semiconductor be liable for any failure in a semiconductor device or any secondary damage resulting from use at a value exceeding the absolute maximum rating.
- 5- No license is granted by the datasheet(s) under any patents or other rights of any third party or Sensitron Semiconductor.
- 6- The datasheet(s) may not be reproduced or duplicated, in any form, in whole or part, without the expressed written permission of Sensitron Semiconductor.
- 7- The products (technologies) described in the datasheet(s) are not to be provided to any party whose purpose in their application will hinder maintenance of international peace and safety nor are they to be applied to that purpose by their direct purchasers or any third party. When exporting these products (technologies), the necessary procedures are to be taken in accordance with related laws and regulations.