


CUSTOMER DRAWING


P/N: 3800S 175/-2

REV

| PART NUMBER | MATERIAL | FINISH |
|---------------|--------------------------------------|-----------|
| 3800S 75A-2 | .020 THICK BRASS C26000, I/2 HARD | PRETINNED |
| 3800S 175AB-2 | .020 THICK BRASS C26000, I/2 HARD | NONE |
| 3800S 175AD-2 | .020 THICK BRASS C26000 1/2 HARD | POST-TIN |



- I. CMA RANGE: 710-2,725
- 2. FOR PIGTAIL SPLICES USED IN A BENCH APPLICATOR, ADD SUFFIX "PP" TO PART NUMBER (i.e. 3800S 175A-2PP), SEE FIGURE 1 FOR REELING.
- 3. FOR THROUGH SPLICES USED IN A BENCH APPLICATOR, THE PART NUMBER REMAINS THE SAME AS IN THE TABLE (i.e. 3800S 175A-2). SEE FIGURE 2 FOR REELING.
- 4. FOR PIGTAIL AND THROUGH SPLICES USED IN A SLIM-LINE AIR PRESS, THE PART NUMBER REMAINS THE SAME AS IN THE TABLE (i.e. 3800S 175A-2). SEE FIGURE 2 FOR REELING.
- 5. PAPER INTERLEAVING ADDED TO REDUCE TANGLING IN REELS.



ARK-LES UNCONTROLLED

