

Wide Band RF Amplifier

- * Operating Frequency :0.3 - 3 GHz
- * Saturated Power : 20W Psat Typical
- * Gain : 10 dB
- * Operation Up to 28 Volts ¹



Description: Ultra wideband operation, Fiber Drivers, Test Instrumentation, All Purpose Power Amp

ELECTRICAL SPECIFICATION @ VDD= +28 VDC, -5VDC; Temp. = 25 °C, 50Ω System

Parameter	Symbol	Min	Typ	Max	Unit
Operating Frequency	BW	0.3		3	GHz
Gain	G	8	10		dB
Gain Flatness	Δ G		±1.0	±1.5	dB
Power Added Efficiency	PAE		30		%
Power Output	Psat	40	43		dBm
Return Loss in/out	S11/S22	2.5:1	2.0:1		Ratio
Operating Voltage ¹	Vdc		+28, -5		Volts
Quiescent Current	Idq		300		mA

Note 1: Also Available In A Single +30V Supply

MECHANICAL SPECIFICATION

Parameter	Description	Limits	Units
Dimension	2x1x0.50		inches
RF Connectors IN/OUT	SMA-F		
DC Connector	Filtered DC		

PROTECTIONS

Parameter	Limits	Units
RF Input Power	35	dBm
Reverse Polarity Protection		
Load VSWR	5:01	RATIO
Stability	Unconditional	


ENVIROMENTAL CHARACTERISTICS

Parameter	Symbol	Min.	Typ.	Max	Units
Operating Case Temperature	Tc	0		75	°C
Storage Temperature	Tstg	-55		125°C	°C

3009 Old State Road Telford, PA 18969

Web: www.amplifiersolutions.com
 Email: sales@amplifiersolutions.com

Tel: 215-799-2651
 Fax: 215-799-2563



3009 Old State Road Telford, PA 18969

Web: www.amplifiersolutions.com
Email: sales@amplifiersolutions.com

Tel: 215-799-2561
Fax: 215-799-2563