


State of the Art, Inc.

Thin Film Chip Resistor

M55342/09 RM2512



PERFORMANCE

Resistance Range 5Ω - 1MΩ
Tolerances 0.1%, 1%, 2%, 5%
Maximum Power 1000 mW
Maximum Voltage 200 Volts





TESTS

TCR (-55 to +125 °C) in ppm/°C
Thermal Shock
Low Temperature Operation
Short-time Overload
Resistance to Soldering Heat
Moisture Resistance
Life, 2,000 Hours
High Temperature Exposure

CHARACTERISTICS*

E	H
±25	±50
±0.1%	±0.25%
±0.1%	±0.25%
±0.1%	±0.1%
±0.2%	±0.25%
±0.2%	±0.4%
±0.5%	±0.5%
±0.1%	±0.2%

*Maximum allowable change per MIL-PRF-55342, typical change is 10% of these values.



PART NUMBERING

M55342 H 09 B 100D R - TR

PACKAGING CODE: TR = Tape & Reel W= Waffle Pack

PRODUCT LEVEL DESIGNATOR: M: 1% per 1000 hrs. R: 0.01% P: 0.1% T: Space Level C: Non - ER

RESISTANCE AND TOLERANCE CODE:

Three significant digits, with a letter indicating the decimal location, the tolerance, and the value range.

A: 0.1% Ω D: 1% Ω G: 2% Ω J: 5% Ω
B: 0.1% K Ω E: 1% K Ω H: 2% K Ω K: 5% K Ω
C: 0.1% M Ω F: 1% M Ω T: 2% M Ω L: 5% M Ω

TERMINATION MATERIALS: B: Solderable wraparound W: Gold wire bondable


SIZE CODE: /09 = RM2512

TEMPERATURE CHARACTERISTIC: E: ± 25ppm H: ± 50ppm

PERFORMANCE SPECIFICATION MIL-PRF-55342

MECHANICAL

	INCHES	MILLIMETERS
Length	.250 (.244 - .268)	6.35 (6.20 - 6.81)
Width	.119 (.119 - .129)	3.02 (3.02 - 3.28)
Thickness	.028 (.015 - .033)	0.71 (0.38 - 0.84)
Top Term	.020 (.015 - .025)	0.51 (0.38 - 0.64)
Bottom Term	.019 (.015 - .025)	0.48 (0.38 - 0.64)
Gap	.212 (.208 - .216)	5.39 (5.28 - 5.49)
Approx. Weight	.0513 grams	



2470 Fox Hill Road, State College, PA 16803-1797

Phone (814) 355-8004 Fax (814) 355-2714 Toll Free 1-800-458-3401

04/09/08

Specifications subject to change without notice.

www.resistor.com