


State of the Art, Inc. 0502 Thin Film Chip Resistor

Standard Grade, Wraparound



PERFORMANCE CHARACTERISTICS


 $\begin{array}{lll} \text{Resistance Range(1)} & 5.6\Omega - 150\text{K}\Omega \\ \text{Tolerances (2)} & 0.1\%, \, 0.25\%, \, 0.5\%, 1\%, \, 2\%, \, 5\% \\ \text{TCR} & \pm 25, \, \pm 50, \, \pm 100 \, \text{ppm} \\ \text{Thermal Resistance} & 73.2^{\circ}\text{C/W} \\ \text{Maximum Power} & 60 \, \text{mW} \\ \text{Maximum Voltage} & 40 \, \text{Volts} \end{array}$


(1) Minimum resistance range at 0.1% tolerance is 100ohms.

(2) +/- 0.05% limited availability - consult factory


ENVIRONMENTAL PERFORMANCE (3)

(3)Typical resistance change, test methods and criteria per MIL-PRF-55342.






TYPICAL LIFE TEST PERFORMANCE



POWER DERATING



PART NUMBERING

S 0502 C A 1001 F H B - TR

PACKAGING CODE: - TR = Tape/Reel - W = Waffle Carrier (Default packaging is Bulk)

TERMINATION FINISH: B: Sn60 over nickel barrier W: Gold

TEMPERATURE CHARACTERISTIC TCR: E: ±25 ppm H: ±50 ppm K: ±100 ppm

OLERANCE: B: 01% C: 0.25% D: 0.5% F: 1% G: 2% J: 5%

RESISTANCE VALUE:

Three or Four digits are used, with all leading digits significant. Four digits are used for 1% tolerance or lower; otherwise, three digits are used. The last digit specifies the number of zeros to add. The letter "R" is used to represent the decimal for fractional ohmic values. Example: 5R6 is 5.6 ohms.

PRODUCT DESIGNATION: A: Thin film on alumina


TERMINATION TYPE: C: Wraparound termination

SIZE CODE

GRADE: S: Standard Production H: High Reliability (For Screening options, contact the factory)

MECHANICAL

INCHES MILLIMETERS .052 (.050 - .058) 1.32 (1.27 - 1.47)Length Width .025 (.023 - .027) 0.64(0.58 - 0.69) Thickness .017 0.38 (0.23 - 1.038) (0.38 - 0.58) Top Term .008 (.005 - .015) 0.13 (0.05 - 0.30) .014 (.010 - .020) 0.22 **Bottom Term** (0.13 - 0.38).024 (.020 -.028) 0.36 (0.25 - 0.51)Approx. Weight 0.0014 grams



STATE OF THE ART, INC. 2470 Fox Hill Road, State College, PA 16803-1797 Phone (814) 355-8004 Fax (814) 355-2714 **Toll Free 1-800-458-3401 www.resistor.com**

[&]quot;Specifications subject to change without notice."