

RL-1608-S

SHIELDED SMD POWER INDUCTORS

DESCRIPTION

- Shielded Power Inductors

ENVIRONMENTAL DATA

- Storage temperature range:
-55°C to +130°C
- Operating temperature range:
-40°C to +130°C

PACKAGING INFORMATION

- Packaging information: pg. 489

FEATURES & APPLICATIONS

- Small package with a footprint of 0.26" X 0.175"
- Low-cost, high-energy storage and low resistance make it ideal for communications, computer and converter applications
- Specifically designed with a flat top for reliable pick and place operations
- Available in 25 values with inductance ratings from 1.0 μ H to 10 mH and currents up to 3 A

Verify operation with sample in actual circuit. Order samples at www.rencousa.com.


MECHANICAL DIMENSIONS

U.S. Standard (mm)


PART NUMBER	A (MAX.)	B	C	D	E	F (MAX.)
RL-1608-S	0.260 (6.60)	0.050 (1.27)	0.040 (1.02)	0.170 (4.32)	0.120 (3.05)	0.175 (4.45)

PART NUMBER	PART WEIGHT	G	H (MAX.)	I (REF.)	J (REF.)	K (REF.)	L (REF.)
RL-1608-S	0.35g (0.012oz)	0.160 (4.06)	0.115 (2.92)	0.140 (3.56)	0.160 (4.06)	0.270 (6.86)	0.055 (1.40)


TOP VIEW




SIDE VIEW



RECOMMENDED LAND PATTERN



SCHEMATIC



RENCO ELECTRONICS INC.

595 International Place, Rockledge, FL 32955-4200 USA • www.rencousa.com • ISO 9001 Certified
Toll Free Engineering Hot Line: 800.645.5828 • P: 321.637.1000 • F: 321.637.1600



RL-1608-S

Renco Part No. RL-1608-S	Inductance (μ H)	DCR Max. (Ohms)	Isat (A)	Irms (A)	Q Min.	Q Test Frequency (Hz)	SRF Typ. (MHz)
RL-1608-S-1.0	1.0	0.040	1.400	3.00	30	200 K	250.0
RL-1608-S-1.5	1.5	0.045	0.930	2.80	30	200 K	125.0
RL-1608-S-2.2	2.2	0.050	0.920	1.80	40	200 K	120.0
RL-1608-S-3.3	3.3	0.055	0.750	1.60	40	200 K	120.0
RL-1608-S-4.7	4.7	0.060	0.580	1.40	40	200 K	105.0
RL-1608-S-6.8	6.8	0.065	0.580	1.20	40	200 K	90.0
RL-1608-S-10	10.0	0.075	0.370	1.00	40	200 K	38.0
RL-1608-S-15	15.0	0.090	0.310	0.80	40	100 K	33.0
RL-1608-S-22	22.0	0.110	0.300	0.70	40	100 K	25.0
RL-1608-S-33	33.0	0.190	0.300	0.60	40	100 K	20.0
RL-1608-S-47	47.0	0.300	0.240	0.50	40	100 K	20.0
RL-1608-S-68	68.0	0.370	0.170	0.40	40	100 K	15.0
RL-1608-S-100	100.0	0.480	0.130	0.30	40	100 K	10.0
RL-1608-S-150	150.0	0.590	0.100	0.26	40	100 K	9.0
RL-1608-S-220	220.0	0.770	0.100	0.22	40	100 K	6.0
RL-1608-S-330	330.0	1.400	0.070	0.20	40	100 K	5.0
RL-1608-S-470	470.0	1.800	0.060	0.19	40	100 K	4.0
RL-1608-S-680	680.0	2.200	0.055	0.18	40	100 K	3.0
RL-1608-S-1000	1000.0	3.400	0.045	0.15	40	100 K	2.0
RL-1608-S-1500	1500.0	4.200	0.035	0.12	50	100 K	2.0
RL-1608-S-2200	2200.0	8.500	0.028	0.10	50	100 K	2.0
RL-1608-S-3300	3300.0	11.000	0.024	0.08	50	100 K	1.0
RL-1608-S-4700	4700.0	13.900	0.021	0.06	50	100 K	1.0
RL-1608-S-6800	6800.0	25.000	0.019	0.04	50	100 K	1.0
RL-1608-S-10000	10000.0	32.800	0.017	0.02	50	100 K	0.8

NOTES:

1. INDUCTANCE $\pm 20\%$ TESTED AT 100 kHz, 0.1 Vrms
2. ELECTRICAL SPECIFICATIONS MEASURED AT 25°C
3. Isat - DC CURRENT THAT WILL CAUSE INDUCTANCE TO DROP BY 30%
4. Irms - CURRENT THAT CAUSES THE TEMPERATURE TO RISE APPROX. 40°C ABOVE AMBIENT OF 25°C



RENCO ELECTRONICS INC.

595 International Place, Rockledge, FL 32955-4200 USA • www.rencousa.com • ISO 9001 Certified
Toll Free Engineering Hot Line: 800.645.5828 • P: 321.637.1000 • F: 321.637.1600

