

POWERSTAX N-0275 Series

1U High Ultra Compact AC-DC Power Supply 275W

Outline Product Specification

FEATURES

- ❑ **275 W AC-DC /3" X 5" FOOTPRINT**
- ❑ **UP TO 90% EFFICIENCY**
- ❑ **HIGH POWER DENSITY: OVER 12 W/in³**
- ❑ **ALL OUTPUTS MAY BE PARALLELED**
- ❑ **REMOTE ON /OFF •**
- ❑ **5W 5V STANDBY SUPPLY**
- ❑ **UNIVERSAL AC INPUT**
- ❑ **ACTIVE PFC (90 – 264 VAC)**
- ❑ **BUILT IN OR'ING MOSFET FOR N, N+1**
- ❑ **INRUSH CURRENT PROTECTION**
- ❑ **RoHS COMPLIANT**
- ❑ **I2C INTERFACE FOR DIGITAL POWER MANAGEMENT**

Powerstax continues to lead the power density race with its new small, high efficiency open frame N-0275 Series AC-DC power supplies.

The N-0275 Series provides up to 90% efficiency and the very small footprint reduces wasted power.

The unique design reduces energy consumption and generates less waste heat. It requires little forced air cooling, decreases AC loads and increases reliability and economy of operation.

With an overall height of 1.5" and a 3" x 5" footprint, the N-0275 Series boasts a power density over 12 watts per cubic inch. It is ideally suited for OEMs using the industry standard 1U chassis.

An optional I2C digital communications interface is also provided to allow up to four N-0275 to communicate over the same bus using the I2C protocol. This interface allows routine remote control of the main outputs and the 12V fans. It can also notify the host if a fan fails (lost tachometer pulses). The host can also query the microcontroller for its output voltage and current plus the ambient and transformer temperatures.

Contact Powerstax regarding custom or modified standard power supplies for unique applications.

Safety Approvals: UL, cUL, DEMKO, CE Mark
Emissions: FCC Class B

POWERSTAX
N-0275

Connectors and pinouts may vary based on model. Refer to Powerstax N-0250 engineering specifications for complete information.

page 1 of 2

POWERSTAX N-0275 Series 275W
Ultra Compact AC-DC Power Supply

Outline Product Specification

INPUT SPECIFICATION	
Nominal Input Voltage:	100 - 240 VAC
Maximum AC Input:	90 - 264 VAC
Input Frequency Range:	47 - 63 Hz
Input Current:	3.5A @ 100 VAC
Input Protection:	5 A fuse
Safety Isolation:	3000 VAC input to output 1500 VAC input to ground
Inrush Current:	13 A @ 240 VAC†
Power Factor Correction:	active PFC circuitry, meets or exceeds EN61000-3-2

OPERATING SPECIFICATIONS	
Operating Temperature:	-25 to +50 °C
Temperature Derating:	2.5% / degree 50 °C to 70 °C
Storage Temperature:	-40 to +85 °C
Forced Air Cooling:	10 CFM minimum†
Convection Cooling:	150W
Leakage Current:	< 1.5 mA
MTBF:	>200,000 hours calculated

SIGNALS	
Remote Sense:	V1 and Return
Active Current Sharing:	V1 using OR'ing MOSFET
Passive Redundancy:	V2 and V3 outputs may be wire OR'ed
Fan Output 1:	V2 on a 2-pin keyed connector
Fan Output 2:	On above 45 °C ambient or hot transformer
Fan Tachometer Input:	(Optional) Reports fan speed via I2C
Optional I2C Data / Clock:	Provides I2C control / status interface
Power Good (PG) Output:	High-true CMOS logic and LED drive outputs
Standby Output:	LED drive on when V1 and V2 outputs disabled
Remote Enable Input:	Low-true input enables V1 and V2 outputs
Onboard LED Indicators:	AC On, Power Good

OUTPUT SPECIFICATION	
Power:	275 W
Hold-up Time:	minimum 22 mS
Efficiency:	up to 90%†
Minimum Load:	no load
Over / Under Shoot:	maximum 10% at turn-on

PROTECTION	
Overvoltage Protection:	V1 (latches off)
Overpower Protection:	Protected / Auto Recovery
Short Circuit Protection:	Auto recovery of all outputs protected against short circuit
Thermal Shutdown:	Auto recovery protection against over temperature conditions

† See Engineering Specification

COMPLIANCE:
USA/Canada: UL60950 / C22.2, 60950 (Bi-National Standard) Safety of Information Technology Equipment
Europe: 73/23/EEC "Low Voltage Directive" (Safety) IEC 60950 Third Edition (1999) Safety of Information Technology Equipment. CB certificate and report available. EN60950 (2000) Safety of Information Technology Equipment 89/336/EEC "Electromagnetic Compatibility Directive" (EMC) EN61000-3-3 (1995) Limits of Voltage Fluctuations & Flicker EN61000-3-2 (2000) Harmonic Current Emissions (Power Factor Correction) EN61204-3 (2001) Stabilized Power Supplies, d.c. Outputs EMC Standards Specification EN61204 (2001) is a product family EMC standard which references the following specifications: EN61000-4-2 (1995) ESD EN61000-4-3 (1996) +A1 (1998) Radiated Radio Frequency. Electromagnetic Field Immunity EN61000-4-4 (1995) Fast Transient / Burst Immunity EN61000-4-5 (1995) Surge Immunity EN61000-4-6 (1996) Immunity to Conducted Disturbances EN61000-4-11 (1994) Voltage Dips, Short Interrupts & Voltage Variations

REDUCED NOISE

To minimize acoustic noise, the microcontroller can turn a 12V fan on or off based upon the present load conditions and the amount of cooling air available.

*Cover and Cover & Fan option available.
 Please contact Powerstax for further details.
 Tel: +44 (0) 1252 407800 or
 Email: sales@powerstaxplc.com*

MODEL	OUTPUT	VOLTAGE	REGULATION (%)	MAXIMUM CURRENT (A)	RIPPLE & NOISE (P-P)
N-02751-PFC-120-0000	V1	12	±3	22.9	100 mV
	V2	12	±5	1.0	80 mV
	V3	5sb	±5	1.0	50 mV
N-02751-PFC-240-0000	V1	24	±3	11.5	200 mV
	V2	12	±5	2.5	80 mV
	V3	5sb	±5	2.0	50 mV
N-02751-PFC-480-0000	V1	48	±3	5.7	200 mV
	V2	12	±5	1.0	80 mV
	V3	5sb	±5	1.0	50 mV
N-02751-PFC-560-0000	V1	56	±3	4.9	200 mV
	V2	12	±5	1.0	80 mV
	V3	5sb	±5	1.0	50 mV

All outputs isolated from the chassis

Exceeding absolute maximum ratings may cause permanent damage and may reduce reliability. Information and specifications contained in this data sheet are believed to be correct at the time of publication. However, Powerstax accept no responsibility for consequences arising from printing errors or inaccuracies. Specifications are subject to change without notice.

Powerstax plc

Unit B5, Armstrong Mall, Southwood Business Park, Farnborough, Hants, GU14 0NR, England
 T: +44 (0) 1252 407800 F: +44 (0) 1252 407810 E: sales@powerstaxplc.com W: www.powerstaxplc.com

June 2007