

Part Number PRX+11300 Contact Form A Switch Configuration SPST Rev. A

### Ferrous Metal Sensor


Features	Advantages
<ul style="list-style-type: none"> <li>Hermetically sealed contacts</li> <li>Black Valox housing</li> <li>Extra strong mounting flange</li> <li>Alternate sensing sides PRX+11200 &amp; 11400</li> <li>Also rated to 120 VAC</li> </ul>	<ul style="list-style-type: none"> <li>Extended operations in extreme environments</li> <li>Not ESD sensitive</li> <li>Patented sensing design</li> </ul>

### Electrical Specifications

Power		Watts - maximum	10
Voltage	Switching	VDC - maximum	36
	Breakdown	VDC - minimum	300
Current	Switching	Amp - maximum	0.2
	Carry	Amp - maximum	1.3
Resistance	Initial Contact Resistance	Ohm - maximum	1
	Insulation Resistance	Ohm - minimum	1 E11
Capacitance	Contact	pF - typical	0.2
Temperature	Operating	°C - maximum	+100
	Storage	°C	-40 to +125

### Physical/Operational Specifications

Housing Volume	Excluding Connection	CC - nominal	3.43
External Connection	24AWG	UL1180	PTFE
Must Operate	Distance (d)	Inches	.100
Must Release	Distance (d)	Inches	.425
Operate Time	Including Bounce	mSeconds - maximum	0.4
Release Time		mSeconds - maximum	0.10



- Notes:
- (1) Specifications are not constant across entire magnetic range.
  - (2) Customer must exercise care in handling and mounting to prevent damage to internal components and subsequent changes to sensor performance.
  - (3) For information about performance, custom configuration (i.e. wire length or color; connectors; operational variation), or packaging contact our Sales department.
  - (4) Information contained hereon is for informational purposes only and should not be deemed as accurate for a specific application. Consult factory for specific application information and/or latest revision.