


Ceramic SMD Crystal Unit

Precision type
Ceramic Package
Miniature

Pb-free : RoHs compliance



TFC-3225G4

■ Typical applications

- Cordless Telephones. Coputer Clocks. DVC. OA. AV. Etc.

■ Features

- 12.0 to 50 MHz.
- Economical type Grass sealed unit.
- Miniature type essential in the high density PCB.
- Package : Ceramic lid + Ceramic package.
3.2×2.5×1.1mm


■ Specifications

Model	TFC - 3225G4	
Frequency Range (Fr)	12.000 to 50.000 MHz	Fundamental
Frequency Tolerance (max) (dF/F)	±30.0ppm to ±50.0ppm	at 25±3° C
Frequency Temperature Stability (max)	±30.0ppm to ±100.0ppm (-10 to +60° C) ±50.0ppm to ±100.0ppm (-30 to +85° C)	
Operating Temperature Range	-30 to +85° C	
Storage Temperature Range	-40 to +90° C	
Equivalent Series Resistance (max) (Rr)	See below table	
Load Capacitance (typical) (CL)	8.0pF to Series Resonance	
Parallel Capacitance (max) (Co)	7.0pF max.	
Drive Level (typical) (DL)	10.0μW to 500μW	

■ Environmental Characteristics

Description	Specification
Aging (at 25° C)	±3.0 ppm max / Year (at 25° C)
Fall Shock	Test : 3 time free drop onto concrete board from 150cm high Result: ±3.0 ppm max.
Vibration Shock	Test : Freq. 5-500Hz, Amplitude 1.5mm, Test time 4cycles/XYZ axis Result: ±3.0 ppm max.
Solderability	Test : Immersed into solder bath at 235±° C for 3 sec. Result: More than 95%
Humidity	Test : 90 to 95%RH at 60±3° C±500 hours Result: ±1.0 ppm max.
Reflow Heat	Test : 2 times of IR reflow soldering in accordance with reflow temperature profile as per the document No.:TR-0531 Result: ±5.0 ppm max.

■ Outline Drawing & Suggested Pad



■ Equivalent Series Resistance

Freq. Range	Rr (max)	Mode
16.0 to 18.9MHz	100 Ω	Fundamental
19.0 to 29.9MHz	80 Ω	
30.0 to 50.0MHz	60 Ω	

Connection

- #1 Input
- #2 NC
- #3 Output
- #4 Ground